




CITEL

Protection of video surveillance systems against overvoltages

MSP-VM12



Electrical Characteristics

SPD type	IEC	2+3
Network		12 Vac/Vdc
Nominal line voltage	Un	12 Vac/Vdc
Max. DC operating voltage	Uc	15 Vac/Vdc
Insertion loss		< 0.1 dB
Max. load current @25°C	IL	5 A
Max. load current @25°C	IL	300 mA
Nominal discharge current 15 x 8/20 μs impulses	In	5 kA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA
Nominal discharge current C2 Category	In	2.5 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	10 kV / 5 kA
Protection mode(s)		Common/Differential mode
Protection level @ In (8/20μs)	Up	0.22 kV
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)	Up	20 V
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-C (Line/Earth)	Up	20 V
Protection level L/N @ In (8/20μs)	Up L/N	0.22 kV
Protection level L/PE @ In (8/20μs)	Up L/PE	0.22 kV

ELEC

Network		Signal video
---------	--	--------------

ELEC

Max. DC operating voltage	Uc	6 Vdc
---------------------------	----	-------

ELEC

Max. frequency	f max.	100 Mhz
----------------	--------	---------

ELEC

Insertion loss		< 1dB
----------------	--	-------

ELEC

Protection level @ In (8/20μs)	Up	20 V
--------------------------------	----	------

ELEC

Network		1 pair signal 0-5 V
---------	--	---------------------

ELEC

Max. DC operating voltage	Uc	8 Vdc
---------------------------	----	-------

ELEC

Max. frequency	f max.	16 Mhz
----------------	--------	--------

ELEC

Insertion loss		< 1dB
----------------	--	-------

ELEC

Nominal discharge current 15 x 8/20 μs impulses	In	2.5 kA
---	----	--------

ELEC

Max. discharge current max. withstand @ 8/20 μs by pole	Imax	5 kA
---	------	------

ELEC

Protection level @ In (8/20μs)	Up	20 V
--------------------------------	----	------

Mechanical Characteristics

Technology		MOV+GDT
Connection to Network		By screw terminals: 2.5-25mm ²
Format		DIN rail or flange
Mounting		DIN rail or plate (flange)
Housing material		Anodized aluminum
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection and Power cut off



CITEL

MSP-VM12

Disconnection indicator	Green LED OFF and line cut off
Operating indicator	Green led(s) on
Dimensions	See diagram
Disconnectors	
Thermal disconnecter	Internal
Standards	
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Part number	
420403	

