19" patch panel CAT6 surge protector for Data-Telecom lines

PCH12-C6

- 19" patch panel CAT6 surge protector
- 12 ports
- In : connecor type 110 back
- Out : RJ45 front
- Maintenance possible per port
- Secondary protection
- UL497B

Electrical Characteristics		
Network		100/1000 BaseT, Ethernet
Nominal line voltage	Un	5 Vdc
Max. DC operating voltage	Uc	7.5 Vdc
Max. frequency	f max.	250 MHz
Max. data rate		10/100/1000 Mbps
Insertion loss		< 1 dB
Max. load current @25°C	IL	750 mA
Nominal Discharge Current, X-C (Line/Earth) *8/20µs Test x 10 - C2 Category*	In L/PE	500 A
Protection Level *C3 (10/1000µs), 300 applications@10 A, Y-Y (Line/Line)*	Up	20 V
Protection Level *C3 (10/1000µs), 300 applications@10 A, Y-C (Line/Earth)*	Up	20 V
Max. capacitance	C	< 8 pF
Discharge current *at 10/1000µs impulse current*		100 A
Line/Line Nominal discharge current *C2 Category*	In L/L	500 A
Mechanical Characteristics		
Technology		Diode écrêtage
SPD configuration		12 ports de 8 wires
Connection to Network		Self-stripping connector 110 back/RJ45 Female. front
Format		Rack 19"
Mounting		Baie 19"
Housing material		Aluminium
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit
Disconnection indicator		Transmision interrupt
Spare module(s)		removable circuit 2 ports
Remote signaling of disconnection		No
Pinout		(1-2)(3-6)(4-5)(7-8)
Dimensions		See diagram
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B / IEEE 802-3an
Part number		
6249		