



Compact Type 2 hard wired surge protector

CITEL

MLPCA1-230L-2L



- Type 2 (or 3) 2 phase + N surge protector
- Compact
- Wall mounting
- Status indicators
- IP65
- AC disconnection in case of end of life



	Electrical Characteristics																																																									
<p>V: Varistor GSG: Specific gas tube LED: Disconnection indicator Ft: Thermal fuse t*: Thermal system disconnection</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>2+3</td></tr> <tr><td>Network</td><td></td><td>220-240V 2-phase + N</td></tr> <tr><td>AC system</td><td></td><td>TT-TN</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>230 V</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>320 Vac</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>10 A</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>In</td><td>5 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>10 kA</td></tr> <tr><td>Total Maximum discharge current max. total withstand @ 8/20 μs</td><td>Imax Total</td><td>30 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td><td>Uoc</td><td>10 kV</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>10 kV / 10 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level @ In (8/20μs)</td><td>Up</td><td>1.5 kV</td></tr> <tr><td>Protection level L/N @ In (8/20μs)</td><td>Up L/N</td><td>1.5 kV</td></tr> <tr><td>Protection level L/PE @ In (8/20μs)</td><td>Up L/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>Iscrr</td><td>10 000 A</td></tr> </table>	SPD type		2+3	Network		220-240V 2-phase + N	AC system		TT-TN	Nominal line voltage	Un	230 V	Max. AC operating voltage	Uc	320 Vac	Max. load current @25°C	IL	10 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Follow current	If	None	Nominal discharge current 15 x 8/20 μs impulses	In	5 kA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA	Total Maximum discharge current max. total withstand @ 8/20 μs	Imax Total	30 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	10 kV	Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA	Protection mode(s)		Common/Differential mode	Protection level @ In (8/20μs)	Up	1.5 kV	Protection level L/N @ In (8/20μs)	Up L/N	1.5 kV	Protection level L/PE @ In (8/20μs)	Up L/PE	1.5 kV	Admissible short-circuit current	Iscrr	10 000 A
SPD type		2+3																																																								
Network		220-240V 2-phase + N																																																								
AC system		TT-TN																																																								
Nominal line voltage	Un	230 V																																																								
Max. AC operating voltage	Uc	320 Vac																																																								
Max. load current @25°C	IL	10 A																																																								
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																																								
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																																								
Follow current	If	None																																																								
Nominal discharge current 15 x 8/20 μs impulses	In	5 kA																																																								
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA																																																								
Total Maximum discharge current max. total withstand @ 8/20 μs	Imax Total	30 kA																																																								
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	10 kV																																																								
Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA																																																								
Protection mode(s)		Common/Differential mode																																																								
Protection level @ In (8/20μs)	Up	1.5 kV																																																								
Protection level L/N @ In (8/20μs)	Up L/N	1.5 kV																																																								
Protection level L/PE @ In (8/20μs)	Up L/PE	1.5 kV																																																								
Admissible short-circuit current	Iscrr	10 000 A																																																								
	Mechanical Characteristics																																																									
	<table border="1"> <tr><td>Technology</td><td></td><td>MOV+GDT</td></tr> <tr><td>Connection to Network</td><td></td><td>Cable with 5-wire of 1.5mm²</td></tr> <tr><td>Mounting</td><td></td><td>Wall or plate</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP65</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection and AC line cut-off</td></tr> <tr><td>Disconnection indicator</td><td></td><td>LED green OFF and AC network cut-off</td></tr> <tr><td>Voltage/operating indicator</td><td></td><td>Green Led ON</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.152 kg</td></tr> </table>	Technology		MOV+GDT	Connection to Network		Cable with 5-wire of 1.5mm ²	Mounting		Wall or plate	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP65	Failsafe mode		Disconnection and AC line cut-off	Disconnection indicator		LED green OFF and AC network cut-off	Voltage/operating indicator		Green Led ON	Dimensions		See diagram	Weight		0.152 kg																								
Technology		MOV+GDT																																																								
Connection to Network		Cable with 5-wire of 1.5mm ²																																																								
Mounting		Wall or plate																																																								
Housing material		Thermoplastic UL94 V-0																																																								
Operating temperature	Tu	-40/+85°C																																																								
Protection rating		IP65																																																								
Failsafe mode		Disconnection and AC line cut-off																																																								
Disconnection indicator		LED green OFF and AC network cut-off																																																								
Voltage/operating indicator		Green Led ON																																																								
Dimensions		See diagram																																																								
Weight		0.152 kg																																																								
	Disconnectors																																																									
	<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> </table>	Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed																																																			
Thermal disconnector		Internal																																																								
Installation ground fault breaker		Type 'S' or delayed																																																								
	Standards																																																									
	<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> </table>	Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																						
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																								
	<table border="1"> <tr><td>Part number</td><td></td><td>835265</td></tr> </table>	Part number		835265																																																						
Part number		835265																																																								

