




CITEL

Type 2 AC surge protector - Single-phase

DAC50-11-320



- Type 2 AC multipolar surge protector
- In: 20 kA
- Imax: 50 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11 certified



Electrical Characteristics

SPD type	IEC	2
Network		230 V single-phase
AC system		TT-TN
Max. AC operating voltage	Uc	320 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection
Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms withstand
Residual Current		
Leakage current to Ground	Ipe	None
Follow current	If	None
Nominal discharge current 15 x 8/20 µs impulses	In	20 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	50 kA
Total Maximum discharge current max. total withstand @ 8/20 µs	Imax Total	50 kA
Protection mode(s)		L/N and N/PE
Protection level @ In (8/20µs) and @ 6 kV (1,2/50 µs)	Up L/N	1.5 kV
Protection level N/PE @ In (8/20µs) and @ 6 kV (1,2/50 µs)	Up N/PE	1.5 kV
Residual voltage L/N at 5 kA @ 5 kA (8/20µs)	Up-5kA	1.2 kV
Protection level N/PE at 5 kA @ 5 kA (8/20µs)	Up-5kA	1.2 kV
Admissible short-circuit current	Iscrr	50 000 A

UL Electrical Characteristics

Maximum Continuous Operating Voltage(L-L/L-N)	MCOV	320 V
Maximum Continuous Operating Voltage(L-G/N-G)	MCOV	255 V
Maximum Limiting Voltage(L-L/L-N)	MLV	2160 V
Maximum Limiting Voltage(L-G/N-G)	MLV	2470 V / 1510 V

Mechanical Characteristics

Technology		MOV+GDT
SPD configuration		Single phase
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Ingress Protection rating		IP20 (NEMA 2)
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole - Red/Green
Spare module(s)		MDAC50-320+MDAC50G-320
Remote signaling of disconnection		option DAC50S-11-320 : output on changeover contact
Dimensions		See diagram - 2TE (EN43880)

Disconnectors

Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		50 A min. - 125 A max. - Fuses Type gG

Standards

Standards compliance		IEC 61643-11 / EN 61643-11
----------------------	--	----------------------------



CITEL

Type 2 AC surge protector - Single-phase

DAC50-11-320

Certification	OVE
Part number	821110332

