





- ✦ Type 2 AC Multipolar surge protector
- ✦ In : 15 kA
- ✦ I_{max} total : 75 kA
- ✦ Internal Fuse
- ✦ Pluggable module for each phase
- ✦ Remote signaling option
- ✦ NF EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance
- ✦



V: High-energy varistor
 Ft: Thermal fuse
 F: Overcurrent protection (fuse)
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics			
SPD type	IEC		2
Network			120/208 V 3-phase
AC system			TNC
Max. AC operating voltage	U _c		150 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT		180 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT		230 Vac disconnection
Residual Current Leakage current to Ground	I _{pe}		< 1 mA
Follow current	I _f		None
Nominal discharge current 15 x 8/20 μs impulses	I _n		15 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}		25 kA
Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max} Total		75 kA
Connection mode(s)			L/PE
Protection level L/PE @ I _n (8/20 μs)	U _p L/PE		1.2 kV
Residual voltage L/PE at 5 kA @ 5 kA (8/20 μs)	U _{p-5kA}		0.6 kV
Admissible short-circuit current	I _{sc}		100 000 A
Mechanical Characteristics			
Technology			MOV
SPD configuration			3-phase
Connection to Network			By screw terminals: 2.5-25mm ² (35mm ² rigid)
Format			Plug-in modular box
Mounting			Symmetrical rail 35 mm (EN 60715)
Housing material			Thermoplastic UL94 V-0
Operating temperature	T _u		-40/+85°C
Protection rating			IP20
Failsafe mode			Disconnection from AC network
Disconnection indicator			1 mechanical indicator by pole - Red/Green
Spare module(s)			MDACF25-150
Remote signaling of disconnection			option DACF25S-30-150 : output on changeover contact
Wiring for remote signaling			1.5 mm ² max.
Max. Voltage/Current for remote signaling			250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions			See diagram - 3 TE (EN43880)
Disconnectors			
Thermal disconnector			Internal
Installation ground fault breaker			Type 'S' or delayed
Back-up protection device			internal (equivalent AC rating : 40 A, gG Type)
Standards			
Standards compliance			IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Part number			
821410113			