





- ✦ High current data transmission
- ✦ Common mode and differential mode protection
- ✦ Data lines, including those isolated from Earth
- ✦ Compact DIN rail enclosure, high density protection
- ✦ Protection of shield wire
- ✦ Plug-out with line cut-off
- ✦ Location and test categories: D1, C2, C3
- ✦ IEC 61643-21 compliance



	<b>Electrical Characteristics</b>																																								
 <p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RTC, ADSL2, VDSL2</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>150 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>170 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>10 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>&lt; 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 µs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td>220 V</td> </tr> <tr> <td>Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td>220 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>&lt; 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>limp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> </table>		Network		RTC, ADSL2, VDSL2	Nominal line voltage	Un	150 V	Max. DC operating voltage	Uc	170 Vdc	Max. frequency	f max.	10 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	220 V	Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	220 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350µs Test - D1 Category	limp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance (± 10%)		4.7 Ohm
Network		RTC, ADSL2, VDSL2																																							
Nominal line voltage	Un	150 V																																							
Max. DC operating voltage	Uc	170 Vdc																																							
Max. frequency	f max.	10 MHz																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	300 mA																																							
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																							
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	220 V																																							
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	220 V																																							
Max. capacitance	C	< 50 pF																																							
Impulse current 2 x 10/350µs Test - D1 Category	limp	5 kA																																							
Nominal discharge current C2 Category	In	5 kA																																							
Line resistance (± 10%)		4.7 Ohm																																							
	<b>Mechanical Characteristics</b>																																								
	<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">Spring terminal: cross section 0.5-2.5mm<sup>2</sup></td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td colspan="2">-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLAM-170</td> </tr> </table>		Technology	GDT+TVS diode		SPD configuration	1-pair+shielded		Connection to Network	Spring terminal: cross section 0.5-2.5mm <sup>2</sup>		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating and storage temperature	-40/+85°C		Protection rating	IP20		Failsafe mode	Short-circuit		Disconnection indicator	Transmission interrupt - default mode 2		Spare module(s)	DLAM-170										
Technology	GDT+TVS diode																																								
SPD configuration	1-pair+shielded																																								
Connection to Network	Spring terminal: cross section 0.5-2.5mm <sup>2</sup>																																								
Mounting	Symmetrical rail 35 mm (EN 60715)																																								
Housing material	Thermoplastic UL94 V-0																																								
Operating and storage temperature	-40/+85°C																																								
Protection rating	IP20																																								
Failsafe mode	Short-circuit																																								
Disconnection indicator	Transmission interrupt - default mode 2																																								
Spare module(s)	DLAM-170																																								
	<b>Standards</b>																																								
	Standards compliance IEC 61643-21 / EN 61643-21																																								
	<b>Part number</b> 6401054																																								