




- ✦ Type 1 + 2 AC surge protector
- ✦ In : 20 kA
- ✦ Iimp : 12.5 kA
- ✦ Pluggable module for each phase
- ✦ Remote signaling
- ✦ EN 61643-11, IEC 61643-11 certified
- ✦ UL1449 ed.5 compliance



Electrical Characteristics		
SPD type	IEC	1+2
Network		120/208 V 3-phase+N
AC system		TNS
Max. AC operating voltage	Uc	150 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	180 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	230 Vac disconnection
Residual Current Leakage current to Ground	Ipe	< 1 mA
Follow current	If	None
Nominal discharge current 15 x 8/20 $\mu$ s impulses	In	20 kA
Max. discharge current max. withstand @ 8/20 $\mu$ s by pole	I <sub>max</sub>	50 kA
Total Maximum discharge current max. total withstand @ 8/20 $\mu$ s	I <sub>max</sub> Total	200 kA
Impulse current by pole max. withstand 10/350 $\mu$ s by pole	I <sub>imp</sub>	12.5 kA
Impulse current N/PE max. withstand 10/350 $\mu$ s	I <sub>imp</sub> N/PE	50 kA
Total lightning current max. total withstand @ 10/350 $\mu$ s	I <sub>total</sub>	50 kA
Specific energy by pole max. withstand 10/350 $\mu$ s	W/R	40 kJ/ohm
Protection mode(s)		L/PE and N/PE
Protection level N/PE @ In (8/20 $\mu$ s)	Up N/PE	0.9 kV
Protection level L/PE @ In (8/20 $\mu$ s)	Up L/PE	1.2 kV
Protection level N/PE at 5 kA @ 5 kA (8/20 $\mu$ s)	Up-5kA	0.6 kV
Residual voltage L/PE at 5 kA @ 5 kA (8/20 $\mu$ s)	Up-5kA	0.6 kV
Admissible short-circuit current	I <sub>sc</sub>	50 000 A
Mechanical Characteristics		
Technology		MOV
SPD configuration		3-phase+Neutral
Connection to Network		By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole - Red/Green
Spare module(s)		MDAC1-13-150
Remote signaling of disconnection		Output on changeover contact
Wiring for remote signaling		1.5 mm <sup>2</sup> max.
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions		See diagram - 4TE (EN43880)
Weight		0.530 kg
Disconnectors		
Thermal disconnecter		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		max. 315 A (gL/gG)
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification		KEMA
Part number		
821710124		