




- ✦ Combined SPD for DC supplies, 2-pole
- ✦ Type 1 + 2
- ✦ In: 15 kA / I<sub>max</sub>: 30 kA
- ✦ I<sub>imp</sub>: 4kA
- ✦ Pluggable module
- ✦ Remote signaling
- ✦ prIEC 61643-41 compliance



Electrical Characteristics			
SPD type	IEC	1+2	
Nominal DC voltage	Un-dc	48 Vdc	
Max. AC operating voltage	Uc	50 Vac	
Max. DC operating voltage	Uc	65 Vdc	
Residual Current Leakage current to Ground	I <sub>pe</sub>	< 0.2 mA	
Follow current	I <sub>f</sub>	None	
Nominal discharge current 15 x 8/20 μs impulses	I <sub>n</sub>	15 kA	
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	30 kA	
Impulse current by pole max. withstand 10/350μs by pole	I <sub>imp</sub>	4 kA	
Total lightning current max. total withstand @ 10/350μs	I <sub>total</sub>	8 kA	
Connection mode(s)	+/PE and -/PE		
Protection level +/PE (-/PE) @ I <sub>n</sub> (8/20μs)	U <sub>p</sub>	300 V / 600 V	
Admissible short-circuit current	I <sub>sc</sub>	50 000 A	
Mechanical Characteristics			
Technology	MOV		
SPD configuration	2-poles		
Connection to Network	Screw terminals: 2.5-25mm <sup>2</sup> +/- 1.5-10mm <sup>2</sup>		
Mounting	Symmetrical rail 35 mm (EN 60715)		
Housing material	Thermoplastic UL94 V-0		
Operating temperature	T <sub>u</sub>	-40/+85°C	
Protection rating	IP20		
Failsafe mode	Disconnection from DC network		
Disconnection indicator	2 mechanical indicators - Red/Green		
Spare module(s)	MDDC30-65		
Remote signaling of disconnection	Output on changeover contact		
Wiring for remote signaling	1.5 mm <sup>2</sup> max.		
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)		
Dimensions	See diagram - 2TE (EN43880)		
Disconnectors			
Thermal disconnector	Internal		
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG		
Standards			
Standards compliance	prIEC 61643-41		
Part number			
828110122			