





- ✔ Type 2 surge protector for PV
- ✔ In: 20kA / I_{max}: 40kA
- ✔ Pluggable
- ✔ Remote signaling
- ✔ UL 1449 ed.5 compliance
- ✔ IEC 61643-31, EN 61643-31, EN 50539-11 certified



V: High-energy varistor
 Ft: Thermal fuse
 t^o: Thermal disconnection system
 MI: Disconnection indicator C: Remote signal contact

Electrical Characteristics

SPD type	IEC	2
Network		PV network 1000 Vdc
Nominal PV voltage	U _{ocstc}	1000 Vdc
Max. PV operating voltage	U _{cpv}	1300 Vdc
Residual Current Leakage current to Ground	I _{pe}	< 0.2 mA
PV Permanent Operating current Current consumption at U _{cpv}	I _{cpv}	< 0.1 mA
Follow current	I _f	None
Nominal discharge current 15 x 8/20 μs impulses	I _n	20 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	40 kA
Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max Total}	60 kA
Current withstand short circuit PV	I _{scpv}	15 000 A
Connection mode(s)		+/-/PE
Protection level @ I _n (8/20μs)	U _p	4.0 kV

Mechanical Characteristics

Technology		MOV
Connection to Network		By screw terminals: 2.5-25mm ²
Operating temperature	T _u	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection SPD of the PV line
Disconnection indicator		3 mechanical indicators
Remote signaling of disconnection		Output on changeover contact
Dimensions		See diagram

Disconnectors

Thermal disconnector		Internal
Back-up protection device		Without

Standards

Standards compliance		IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5
Certification		TUV Süd

Part number

48031110
