





- ✦ DC power Type 2 SPD
- ✦ For Energy Storage/EV Charging
- ✦ In/Imax: 20/50 kA
- ✦ Pluggable modules
- ✦ Remote signaling
- ✦ prIEC 61643-41 compliance



V: High-energy varistor
 Ft: Thermal fuse
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics		
SPD type	IEC	2
Nominal DC voltage	Un-dc	650 Vdc
Max. DC operating voltage	Uc	800 Vdc
Residual Current Leakage current to Ground	Ipe	< 0.2 mA
Nominal discharge current 15 x 8/20 μs impulses	In	20 kA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	50 kA
Impulse current by pole max. withstand 10/350μs by pole	Iimp	4 kA
Protection level +/- @ In (8/20μs)	Up	2.7 kV
Admissible short-circuit current	Iscrr	100 000 A
Mechanical Characteristics		
Connection to Network	By screw terminals: 2.5-25 mm ² (35 mm ² rigid)	
Mounting	Symmetrical rail 35 mm (EN 60715)	
Housing material	Thermoplastic UL94 V-0	
Operating temperature	Tu	-40/+85°C
Protection rating	IP20	
Failsafe mode	Disconnection from DC network	
Disconnection indicator	1 mechanical indicator by pole - Red/Green	
Spare module(s)	MDDC50-800	
Remote signaling of disconnection	output on changeover contact	
Wiring for remote signaling	1.5 mm ² max.	
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)	
Dimensions	See diagram - 3 TE (EN43880)	
APPLICATION	ENERGY STORAGGE SYSTEMS (ESS) /EV CHARGING	
Disconnectors		
Thermal disconnector	Internal	
Back-up protection device	50 A min. (Iscrr 100 kA) - 125 A max. (Iscrr 50 kA) - gBat Fuses	
Standards		
Standards compliance	prIEC 61443-41 - IEC61643-11	
Part number		
828511363		