




Type 2 AC Surge Protector for PCB mounting

CITEL

PAC40GS-10-275



- Type 2 AC surge protector
- PCB mounting
- N/PE module
- I_{max}: 40 kA
- Remote signaling
- EN 50539-11 and IEC 61643-31 compliance*



Electrical Characteristics

SPD type		2
Max. AC operating voltage	U _c	275 Vac
Nominal discharge current <i>15 x 8/20 μs impulses</i>	I _n	20 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	40 kA
Protection level <i>@ I_n (8/20 μs)</i>	U _p	1.5 kV
Admissible short-circuit current	I _{sc}	25 000 A

Mechanical Characteristics

Technology		Gas discharge tube
Connection to Network		Through soldering pins
Mounting		On Printed Circuit Board
Housing material		Thermoplastic UL94 V-0
Operating temperature	T _u	-40/+85°C
Protection rating		IP20
Disconnection indicator		1 mechanical indicator
Remote signaling of disconnection		Output on changeover contact
Weight		0.026 kg

Disconnectors



Thermal disconnector		Internal
----------------------	--	----------

Standards

Standards compliance		EN 61643-11 / IEC 61643-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.
----------------------	--	---

Part number

8712607



GSG: Specific gas tube
 t°: Thermal disconnection system
 Ft: Thermal fuse
 MI: Disconnection indicator
 C: Remote signaling contact

