





CITEL

Compact Type 2 (or 3) DC surge protector - 65 V - Monobloc

DDCN06S-L21YG-65



- DC Power Type 2+3 SPD
- 2-port configuration (series mounting)
- Compact and Cost effective
- In/Imax: 2 kA/6 kA
- Max. load current: 16A
- Disconnection + AC line cut
- Remote signaling
- EN 61643-11, IEC 61643-11 compliance



Electrical Characteristics		
Nominal DC voltage	Un-dc	48 Vdc
Max. DC operating voltage	Uc	65 Vdc
Max. load current @25°C	IL	16 A
Residual Current	Ipe	None
<i>Leakage current to Ground</i>		
Nominal discharge current	In	2 kA
<i>15 x 8/20 μs impulses</i>		
Max. discharge current	Imax	6 kA
<i>max. withstand @ 8/20 μs by pole</i>		
Withstand on Combination waveform IEC 61643-11	Uoc	4 kV
<i>Class III test: 1.2/50μs - 8/20μs</i>		
Connection mode(s)		+/-/PE
Protection level +/-	Up	0.5 kV
<i>@ In (8/20μs)</i>		
Protection level +/-PE (-/PE)	Up	0.8 kV
<i>@ In (8/20μs)</i>		
Admissible short-circuit current	Iscsr	10 000 A
Mechanical Characteristics		
SPD configuration		Single phase
Connection to Network		By screw terminals: 1.5-10mm ²
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection and AC line cut-off
Disconnection indicator		Green LED OFF
Remote signaling of disconnection		output on NC contact
Dimensions		See diagram - 1TE (EN43880)
Disconnectors		
Thermal disconnector		Internal
Back-up protection device		Fuse type gG - 16 A
Standards		
Standards compliance		IEC 61643-11 / prIEC 61643-41
Part number		
70135052		

