





Type 2 or 3 AC surge protector - pluggable with integrated fuse

CITEL

DACF15S-31-150



- Type 2 (or 3) AC surge protector
- Interne Disconnection device
- Low caliber of the internal connector = systematic coordination with upstream circuit breaker
- In: 5 kA
- Imax: 15 kA
- Pluggable module for each phase
- Remote signaling
- EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance



V: High-energy varistor
 Ft: Thermal fuse
 t°: Thermal disconnection system
 C: Remote signal contact
 MI: Disconnection indicator

Electrical Characteristics

SPD type	2 (or 3)	
Network	120/208 V 3-phase+N	
AC system	TT-TNS	
Max. AC operating voltage	Uc	150 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 180 Vac withstand	
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 230 Vac withstand	
Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT 1200 V/300A/200 ms withstand	
Residual Current Leakage current to Ground	Ipe	None
Follow current	If	None
Nominal discharge current $15 \times 8/20 \mu\text{s impulses}$	In	5 kA
Max. discharge current max. withstand @ $8/20 \mu\text{s by pole}$	Imax	15 kA
Withstand on Combination waveform IEC 61643-11 Class III test: $1.2/50\mu\text{s} - 8/20\mu\text{s}$	Uoc	10 kV
Protection level L/N @ In ($8/20\mu\text{s}$)	Up L/N	0.6 kV
Protection level N/PE @ In ($8/20\mu\text{s}$)	Up N/PE	1.5 kV
Admissible short-circuit current	Isccr	100 000 A
Mechanical Characteristics		
Technology	MOV+GDT	
SPD configuration	3-phase+Neutral	
Connection to Network	By screw terminals: 2.5-25mm ² (35mm ² rigid)	
Format	Plug-in modular box	
Mounting	Symmetrical rail 35 mm (EN 60715)	
Housing material	Thermoplastic UL94 V-0	
Operating temperature	Tu	-40/+85°C
Protection rating	IP20	
Failsafe mode	Disconnection from AC network	
Disconnection indicator	1 mechanical indicator by pole - Red/Green	
Spare module(s)	MDACF15-150 + MDAC50G-255	
Remote signaling of disconnection	output on changeover contact	
Wiring for remote signaling	1.5 mm ² max.	
Dimensions	See diagram - 4TE (EN43880)	
Disconnectors		
Thermal disconnector	Internal	
Installation ground fault breaker	Type 'S' or delayed	
Back-up protection device	internal (equivalent AC rating : 25 A, gG Type)	
Standards		
Standards compliance	IEC 61643-11 / EN 61643-11	
Part number	821310144	

