





- ✦ Re-inforced Type 2 AC surge protector
- ✦ In : 40 kA
- ✦ I_{max} : 80 kA
- ✦ Pluggable module for each phase
- ✦ Remote signaling option
- ✦ EN 61643-11, IEC 61643-11 certified
- ✦ UL1449 ed.5 compliance



V: High-energy varistor
 Ft: Thermal fuse
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics			
SPD type	IEC		2
Network			120/208 V 3-phase
AC system			TNC
Max. AC operating voltage	Uc		150 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT		180 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT		230 Vac disconnection
Residual Current Leakage current to Ground	I _{pe}		< 1 mA
Follow current	I _f		None
Nominal discharge current 15 x 8/20 μs impulses	I _n		40 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}		80 kA
Protection mode(s)			L/PE
Protection level L/PE @ I _n (8/20μs)	U _p L/PE		1.2 kV
Admissible short-circuit current	I _{scrr}		50 000 A
Mechanical Characteristics			
Technology			MOV
Connection to Network			By screw terminals: 2.5-25mm ² (35mm ² rigid)
Format			Plug-in modular box
Mounting			Symmetrical rail 35 mm (EN 60715)
Housing material			Thermoplastic UL94 V-0
Operating temperature	Tu		-40/+85°C
Protection rating			IP20
Failsafe mode			Disconnection from AC network
Disconnection indicator			1 mechanical indicator by pole - Red/Green
Spare module(s)			MDAC80-150
Remote signaling of disconnection			option DAC80S-30-150 : output on changeover contact
Dimensions			See diagram - 3 TE (EN43880)
Disconnectors			
Thermal disconnector			Internal
Installation ground fault breaker			Type 'S' or delayed
Back-up protection device			Fuses Type gG - 125 A
Standards			
Standards compliance			IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification			KEMA
Part number			
821210113			