





Type 1+2+3 AC surge protector - Unipolar

CITEL

DACN1-25VGS-10-440



- Type 1 + 2+3 AC surge protector
- VG Technology
- In: 25 kA
- Iimp: 25 kA on 10/350µs impulse
- No leakage current
- Unpluggable module for each phase
- Remote signaling
- Optimized to TOV
- EN 61643-11, IEC 61643-11 complied



V: High-energy varistor

GSG: Specific gas tube

Ft: Thermal fuse

C: Remote signaling contact

t°: Thermal disconnection system

MI: Disconnection indicator

Electrical Characteristics

SPD type	1+2+3	
Max. AC operating voltage	Uc	440 Vac
Max. load current @25°C	IL	100 A
Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i>	UT	580 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i>	UT	770 Vac disconnection
Residual Current <i>Leakage current to Ground</i>	Ipe	None
Follow current	If	None
Nominal discharge current 15 x 8/20 µs impulses	In	25 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	70 kA
Impulse current by pole max. withstand 10/350µs by pole	Iimp	25 kA
Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50µs - 8/20µs</i>	Uoc	6 kV
Specific energy by pole max. withstand 10/350 µs	W/R	156 kJ/ohm
Protection level @ In (8/20µs) and @ 6 kV (1.2/50 µs)	Up	1.5 kV
Admissible short-circuit current	Isccr	50 000 A
Mechanical Characteristics		
Technology	VG Technology (MOV+GSG)	
SPD configuration	Single phase	
Connection to Network	By screw terminals: 6-35mm² / by bus	
Format	1-pole modular box	
Mounting	Symmetrical rail 35 mm (EN 60715)	
Housing material	Thermoplastic UL94 V-0	
Operating temperature	Tu	-40/+85°C
Protection rating	IP20	
Failsafe mode	Disconnection from AC network	
Disconnection indicator	1 mechanical indicator - Red/Green	
Remote signaling of disconnection	Output on changeover contact	
Wiring for remote signaling	1.5 mm² max.	
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)	
Dimensions	See diagram - 2TE (EN43880)	
Weight	0.408 kg	
Disconnectors		
Thermal disconnector	Internal	
Installation ground fault breaker	Type 'S' or delayed	
Back-up protection device	Fuses type gG - 315 A	
Standards		
Standards compliance	EN 61643-11 / IEC 61643-11	
Part number	29221022	

