





1-pair DIN rail plug-in Data surge protector

CITEL

DLA-06D2/R



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



G: 3-electrode gas tube
Gb: 2-electrode gas tube
R: Resistor
D: Clamping diode

Electrical Characteristics	
Network	RS422, RS485
Nominal line voltage	Un 6 V
Max. DC operating voltage	Uc 8 Vdc
Max. frequency	f max. > 50 MHz
Insertion loss	< 1 dB
Max. load current @25°C	IL 600 mA
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max} 20 kA
Line inductance	No
Protection level @ I _n (8/20 µs)	Up L/L 30 V
Protection level @ I _n (8/20 µs)	Up L/PE 650 V
Max. capacitance	C < 50 pF
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp} 5 kA
Nominal discharge current C2 Category	I _n 10 kA
Line resistance	< 2 Ohm
Mechanical Characteristics	
Technology	GDT+Clamping diode
SPD configuration	1-pair+shielded
Connection to Network	Spring terminal: cross section 0.5-2.5mm ²
Format	Plug-in DIN box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating and storage temperature	-40/+85°C
Protection rating	IP20
Failsafe mode	Short-circuit
Disconnection indicator	Transmission interrupt - default mode 2
Spare module(s)	DLAM-06D2
Dimensions	See diagram
Standards	
Standards compliance	IEC 61643-21 / EN 61643-21
Part number	
6401612	

