



- ✦ Pluggable surge protection for «DIN» mounting
- ✦ Coordination inductor
- ✦ Up to 2.4 A line current
- ✦ Remote supply version
- ✦ All types of Telephone and Data lines
- ✦ Shield wire protection
- ✦ IEC 61643-21 compliance



	<table border="1"> <thead> <tr> <th colspan="4">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Network</td> <td></td> <td></td> <td>4-20 mA, 24 V analogic</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td></td> <td>24 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td></td> <td>28 Vdc</td> </tr> <tr> <td>Cut-off frequency -3dB, 100 ohm system</td> <td>f max.</td> <td></td> <td>&gt; 1.8 MHz</td> </tr> <tr> <td>Cut-off frequency -1dB, 100 ohm system</td> <td>f max.</td> <td></td> <td>&gt; 1 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td></td> <td>2.4 A</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 µs by pole</td> <td>I<sub>max</sub></td> <td></td> <td>20 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td> <td>In L/PE</td> <td></td> <td>5 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td></td> <td>10 µH</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td></td> <td>40 V</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td></td> <td>40 V</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>I<sub>imp</sub></td> <td></td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L</td> <td></td> <td>5 kA</td> </tr> <tr> <th colspan="4">Mechanical Characteristics</th> </tr> <tr> <td>Technology</td> <td></td> <td></td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td></td> <td>1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td></td> <td>By screw terminal: cross section 0.4-1.5mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td></td> <td></td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td></td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td></td> <td>DLAHM-24D3</td> </tr> <tr> <td>Dimensions</td> <td></td> <td></td> <td>See diagram</td> </tr> <tr> <th colspan="4">Standards</th> </tr> <tr> <td>Standards compliance</td> <td></td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497B</td> </tr> <tr> <td>Certification</td> <td></td> <td></td> <td>UL Listed</td> </tr> <tr> <th colspan="4">Part number</th> </tr> <tr> <td colspan="4">641003</td> </tr> </tbody> </table>	Electrical Characteristics				Network			4-20 mA, 24 V analogic	Nominal line voltage	Un		24 V	Max. DC operating voltage	Uc		28 Vdc	Cut-off frequency -3dB, 100 ohm system	f max.		> 1.8 MHz	Cut-off frequency -1dB, 100 ohm system	f max.		> 1 MHz	Max. load current @25°C	IL		2.4 A	Max. discharge current max. withstand @ 8/20 µs by pole	I <sub>max</sub>		20 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE		5 kA	Line inductance (± 10 %)			10 µH	Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up		40 V	Protection Level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up		40 V	Impulse current 2 x 10/350µs Test - D1 Category	I <sub>imp</sub>		5 kA	Line/Line Nominal discharge current C2 Category	In L/L		5 kA	Mechanical Characteristics				Technology			GDT+TVS diode	SPD configuration			1-pair+shielded	Connection to Network			By screw terminal: cross section 0.4-1.5mm <sup>2</sup>	Format			Plug-in DIN box	Mounting			Symmetrical rail 35 mm (EN 60715)	Housing material			Thermoplastic UL94 V-0	Operating temperature	Tu		-40/+85°C	Protection rating			IP20	Failsafe mode			Short-circuit	Disconnection indicator			Transmission interrupt - default mode 2	Spare module(s)			DLAHM-24D3	Dimensions			See diagram	Standards				Standards compliance			IEC 61643-21 / EN 61643-21 / UL497B	Certification			UL Listed	Part number				641003			
Electrical Characteristics																																																																																																																																	
Network			4-20 mA, 24 V analogic																																																																																																																														
Nominal line voltage	Un		24 V																																																																																																																														
Max. DC operating voltage	Uc		28 Vdc																																																																																																																														
Cut-off frequency -3dB, 100 ohm system	f max.		> 1.8 MHz																																																																																																																														
Cut-off frequency -1dB, 100 ohm system	f max.		> 1 MHz																																																																																																																														
Max. load current @25°C	IL		2.4 A																																																																																																																														
Max. discharge current max. withstand @ 8/20 µs by pole	I <sub>max</sub>		20 kA																																																																																																																														
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE		5 kA																																																																																																																														
Line inductance (± 10 %)			10 µH																																																																																																																														
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up		40 V																																																																																																																														
Protection Level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up		40 V																																																																																																																														
Impulse current 2 x 10/350µs Test - D1 Category	I <sub>imp</sub>		5 kA																																																																																																																														
Line/Line Nominal discharge current C2 Category	In L/L		5 kA																																																																																																																														
Mechanical Characteristics																																																																																																																																	
Technology			GDT+TVS diode																																																																																																																														
SPD configuration			1-pair+shielded																																																																																																																														
Connection to Network			By screw terminal: cross section 0.4-1.5mm <sup>2</sup>																																																																																																																														
Format			Plug-in DIN box																																																																																																																														
Mounting			Symmetrical rail 35 mm (EN 60715)																																																																																																																														
Housing material			Thermoplastic UL94 V-0																																																																																																																														
Operating temperature	Tu		-40/+85°C																																																																																																																														
Protection rating			IP20																																																																																																																														
Failsafe mode			Short-circuit																																																																																																																														
Disconnection indicator			Transmission interrupt - default mode 2																																																																																																																														
Spare module(s)			DLAHM-24D3																																																																																																																														
Dimensions			See diagram																																																																																																																														
Standards																																																																																																																																	
Standards compliance			IEC 61643-21 / EN 61643-21 / UL497B																																																																																																																														
Certification			UL Listed																																																																																																																														
Part number																																																																																																																																	
641003																																																																																																																																	
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube L: Inductor D: Clamping diode</p>																																																																																																																																	