

CERTIFICATE OF COMPLIANCE

Certificate Number E184939
Report Reference E184939-19970506
Issue Date 2020-JUNE-05

Issued to: Citel America Inc
10108 USA Today Way
Miramar FL 33025

This certificate confirms that representative samples of ISOLATED LOOP CIRCUIT PROTECTORS
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 497B, Protectors for Data Communications and Fire-Alarm Circuits

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E184939
Report Reference E184939-19970506
Issue Date 2020-JUNE-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Isolated Loop Circuit Protectors:

USL Models Bx80, where X is 2, 3, or 4 (protected pairs), followed by -06D3, -12D3, -24D3, -48D3, -170, -6DBC, -6D3/A12, -6D3/A12-SC, -24D3/A24, 24D3/A24 SC, -48DBC or -T.

USL Models B180-06D3, -06DBC, -12D3, -24D3, -48D3 or -T.

USL Models MJ6-1-12V, -1D-ARC, -2-6V.

USL Models MJ8-2-24V, 2 6 BL, 2 48DBC, 2D ETH, -2D-TOK, -2RN, -2T1, -280T.

USL Models B180T/MJ6, B280T/MJ6;

USL Models E280-6V, -12V, 24V, -48V, -6DBC, -48DBC or -T. Model E2D-6DBC.

Din Rail Mount types:

USL Models DLA, followed by -06D3, -06DBC, -12D3, 24D3, -48D3, -170.

USL Models DLC, followed by -06D3, -06DBC, -12D3, -12DBC, -24D3, -24DBC, -48D3, -48DBC, or -170. Intended for use in a Listed enclosure or closet that is only accessible by service personnel.

USL Models DLAH, followed by -06D3, -06DBC, -12D3, 24D3, -48D3 or -170.

USL Models DLAS, followed by -06D3, -12D3, -24D3 or -48D3.

USL Models DLAW, followed by -06D3, -06DBC, -12D3, 24D3, -48D3 or -170.

USL Models DLA2, followed by -06D3, -06DBC, -12D3, 24D3, -48D3 or -170.

USL Models DLU, followed by -06, -12, 24, -48, or -170, may be followed by D3, or DBC.

USL Models DLU2, followed by 06, 12, -24, -48, or -170, may be followed by D3 or DBC.

USL Model DTB-48

Intended for use on communication loop circuits which have been isolated from the Public Switched Telephone Network.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

