



Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

### Cat No(s): DS50PV-1500/51

<u>SPD</u> Type	<u>Volts</u> (V)	<u>AC/DC</u> DC PV	<u>Phase</u>	<u>Amps</u> (A)	<u>Ambient</u> Min(°C)	<u>Ambient</u> Max(°C)	<u>Mode</u>	<u>VPR</u> (Vpk)	<u>MLV</u> (Vpk)	<u>MCOV</u> (V)	<u>Vn</u> (Vdc)	<u>In</u> (kA)	<u>SCCR</u> (kA)	<u>Notes</u>
4CA	1500	DC PV	-	n/a	-40	85	DC+-DC-	-	5340	1500	n/a	10	n/a	1
							DC+-G	-	5380	1500	n/a			
							DC--G	-	5380	1500	n/a			
4CA	1500	DC	-	n/a	-40	85	DC+-DC-	-	5120	1500	n/a	10	n/a	1
							DC+-G	-	5220	1500	n/a			
							DC--G	-	5220	1500	n/a			

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2015-04-30

Last Revised: 2021-10-26

© 2022 UL LLC

