



Electrical Characteristics

SPD type	2+3	
Network	12 Vac/Vdc	
Nominal line voltage	Un	12 Vac/Vdc
Max. DC operating voltage	Uc	15 Vac/Vdc
Insertion loss	< 0.1 dB	
Max. load current @25°C	IL	5 A
Nominal discharge current 15 x 8/20 µs impulses	In	5 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	10 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	10 kV / 5 kA
Protection mode(s)	Common/Differential mode	
Protection level @ In (8/20µs)	Up	0.22 kV
Protection level @ In (8/20 µs)	Up L/L	20 V
Protection level L/N @ In (8/20µs)	Up L/N	0.22 kV
Protection level L/PE @ In (8/20µs)	Up L/PE	0.22 kV
Nominal discharge current C2 Category	In	2.5 kA

ELEC

Network	Signal video	
ELEC		
Max. DC operating voltage	Uc	6 Vdc
ELEC		
Max. frequency	f max.	100 Mhz
ELEC		
Insertion loss	< 1dB	
ELEC		
Max. load current@25°C	IL	300 mA
ELEC		
Nominal discharge current 15 x 8/20 µs impulses	In	5 kA
ELEC		
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	10 kA
ELEC		
Protection level @ In (8/20µs)	Up	20 V
ELEC		
Network	1 pair signal 0-5 V	
ELEC		
Max. DC operating voltage	Uc	8 Vdc
ELEC		
Max. frequency	f max.	16 Mhz
ELEC		
Insertion loss	< 1dB	
ELEC		
Max. load current@25°C	IL	300 mA
ELEC		
Nominal discharge current 15 x 8/20 µs impulses	In	2.5 kA
ELEC		
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	5 kA
ELEC		
Protection level @ In (8/20µs)	Up	20 V

Mechanical Characteristics

Technology	MOV+GDT	
Connection to Network	By screw terminals: 2.5-25mm ²	



Format	DIN rail or flange
Mounting	DIN rail or plate (flange)
Housing material	Anodized aluminum
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection and Power cut off
Disconnection indicator	Green LED OFF and line cut off
Voltage/operating indicator	Green led(s) on
Dimensions	See diagram
Disconnectors	
Thermal disconnector	Internal
Standards	
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Part number	
420403	

