



1-pair DIN rail plug-in Data surge protector



CITEL

DLAH-48D3



- ▶ Pluggable surge protection for «DIN» mounting
- ▶ Coordination inductor
- ▶ Up to 2.4 A line current
- ▶ Remote supply version
- ▶ All types of Telephone and Data lines
- ▶ Shield wire protection
- ▶ IEC 61643-21 compliance



 <p>65</p> <p>13</p> <p>90</p> <p>DINRAIL</p> <p>3a 4a</p> <p>1a 2a</p> <p>1b 2b</p> <p>3b 4b</p>	Electrical Characteristics																																								
 <p>1a 1b</p> <p>2a 2b</p> <p>4a 4b</p> <p>3a 3b</p> <p>earth possible on DIN rail</p> <p>G: 3-electrode gas tube Gb: 2-electrode gas tube L: Inductor D: Clamping diode</p>	<table border="1"> <tr><td>Network</td><td></td><td>RNIS-T0, 48 V line</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>48 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>53 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>2.4 A</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance</td><td></td><td>10uH</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/L</td><td>70 V</td></tr> <tr><td>Impulse current 2 x 10/350μs Test - D1 Category</td><td>Iimp</td><td>5 kA</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>In L/L</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category</td><td>In L/PE</td><td>5 kA</td></tr> <tr><td>Line resistance</td><td></td><td>0 Ohm</td></tr> </table>		Network		RNIS-T0, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	2.4 A	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		10uH	Protection level @ In (8/20 μs)	Up L/L	70 V	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		0 Ohm
Network		RNIS-T0, 48 V line																																							
Nominal line voltage	Un	48 V																																							
Max. DC operating voltage	Uc	53 Vdc																																							
Max. frequency	f max.	> 3 MHz																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	2.4 A																																							
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																							
Line inductance		10uH																																							
Protection level @ In (8/20 μs)	Up L/L	70 V																																							
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																							
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																							
Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA																																							
Line resistance		0 Ohm																																							
	Mechanical Characteristics																																								
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>1-pair+shielded</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.4-1.5mm²</td></tr> <tr><td>Format</td><td></td><td>Plug-in DIN box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>Disconnection indicator</td><td></td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Spare module(s)</td><td></td><td>DLAHM-48D3</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> </table>		Technology		GDT+Clamping diode	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal: cross section 0.4-1.5mm ²	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLAHM-48D3	Dimensions		See diagram			
Technology		GDT+Clamping diode																																							
SPD configuration		1-pair+shielded																																							
Connection to Network		By screw terminal: cross section 0.4-1.5mm ²																																							
Format		Plug-in DIN box																																							
Mounting		Symmetrical rail 35 mm (EN 60715)																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating temperature	Tu	-40/+85°C																																							
Protection rating		IP20																																							
Failsafe mode		Short-circuit																																							
Disconnection indicator		Transmission interrupt - default mode 2																																							
Spare module(s)		DLAHM-48D3																																							
Dimensions		See diagram																																							
	Standards																																								
	Standards compliance IEC 61643-21 / EN 61643-21 / UL497A																																								
	Part number																																								
	641004																																								

