



# CITEL

## AC surge protector for LED Lighting system Class 1

### MLP1-230L-P/DL



- Combined surge protector AC and DALI transmission
- Type 2 or 3
- For LED lighting system Class I
- Max. discharge current 10kA
- EN 61643-11, IEC 61643-11 compliance



	<b>Electrical Characteristics</b>																																																																
	<table border="1"> <tr><td>SPD type</td><td></td><td>2+3</td></tr> <tr><td>Network</td><td></td><td>AC: 220-240 V single-phase I Dataline: DALI/DMX/RS485/0-10V</td></tr> <tr><td>AC system</td><td></td><td>TT-TN</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>AC : 230-277 Vac I DATA : 24 Vac</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>AC : 305 Vac I DATA : 28 Vac</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>DATA : 10 MHz</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>AC : 2.5 A I DATA : 300mA</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 µs impulses</td><td>In</td><td>AC : 5kA I DATA : 5 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>Imax</td><td>AC : 10 kA I DATA : 10 kA</td></tr> <tr><td>Total Maximum discharge current max. total withstand @ 8/20 µs</td><td>Imax Total</td><td>AC : 20 kA I DATA : 20 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs</td><td>Uoc</td><td>AC : 10 kV / 5 kA</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>10 kV / 10 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level @ In (8/20µs)</td><td>Up</td><td>DATA : 50 V</td></tr> <tr><td>Protection level L/N @ In (8/20µs)</td><td>Up L/N</td><td>1.5 kV</td></tr> <tr><td>Protection level L/PE @ In (8/20µs)</td><td>Up L/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>Iscrr</td><td>10 000 A</td></tr> </table>		SPD type		2+3	Network		AC: 220-240 V single-phase I Dataline: DALI/DMX/RS485/0-10V	AC system		TT-TN	Nominal line voltage	Un	AC : 230-277 Vac I DATA : 24 Vac	Max. AC operating voltage	Uc	AC : 305 Vac I DATA : 28 Vac	Max. frequency	f max.	DATA : 10 MHz	Max. load current @25°C	IL	AC : 2.5 A I DATA : 300mA	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 µs impulses	In	AC : 5kA I DATA : 5 kA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	AC : 10 kA I DATA : 10 kA	Total Maximum discharge current max. total withstand @ 8/20 µs	Imax Total	AC : 20 kA I DATA : 20 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	AC : 10 kV / 5 kA	Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA	Protection mode(s)		Common/Differential mode	Protection level @ In (8/20µs)	Up	DATA : 50 V	Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV	Protection level L/PE @ In (8/20µs)	Up L/PE	1.5 kV	Admissible short-circuit current	Iscrr	10 000 A
SPD type		2+3																																																															
Network		AC: 220-240 V single-phase I Dataline: DALI/DMX/RS485/0-10V																																																															
AC system		TT-TN																																																															
Nominal line voltage	Un	AC : 230-277 Vac I DATA : 24 Vac																																																															
Max. AC operating voltage	Uc	AC : 305 Vac I DATA : 28 Vac																																																															
Max. frequency	f max.	DATA : 10 MHz																																																															
Max. load current @25°C	IL	AC : 2.5 A I DATA : 300mA																																																															
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																																															
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																																															
Residual Current Leakage current to Ground	Ipe	None																																																															
Follow current	If	None																																																															
Nominal discharge current 15 x 8/20 µs impulses	In	AC : 5kA I DATA : 5 kA																																																															
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	AC : 10 kA I DATA : 10 kA																																																															
Total Maximum discharge current max. total withstand @ 8/20 µs	Imax Total	AC : 20 kA I DATA : 20 kA																																																															
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	AC : 10 kV / 5 kA																																																															
Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA																																																															
Protection mode(s)		Common/Differential mode																																																															
Protection level @ In (8/20µs)	Up	DATA : 50 V																																																															
Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV																																																															
Protection level L/PE @ In (8/20µs)	Up L/PE	1.5 kV																																																															
Admissible short-circuit current	Iscrr	10 000 A																																																															
<b>ELEC</b>																																																																	
Insertion loss		DATA : < 1dB																																																															
<b>Mechanical Characteristics</b>																																																																	
Technology		MOV+GDT																																																															
Connection to Network		AC: Screw terminal - 1.5mm <sup>2</sup> max. DATA: Screw terminal - 1mm <sup>2</sup> max.																																																															
Mounting		On plate																																																															
Housing material		Thermoplastic UL94 V-0																																																															
Operating temperature		Tu -40/+85°C																																																															
Protection rating		IP20																																																															
Failsafe mode		Disconnection and AC line cut-off																																																															
Disconnection indicator		LED green OFF and AC network cut-off																																																															
Voltage/operating indicator		Green Led ON																																																															
Remote signaling of disconnection		No																																																															
Dimensions		See diagram																																																															
Weight		0.086 kg																																																															
<b>Disconnectors</b>																																																																	
Thermal disconnector		Internal																																																															
Installation ground fault breaker		Type 'S' or delayed																																																															
<b>Standards</b>																																																																	
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																															
Certification																																																																	
Part number																																																																	
721231																																																																	

