





Type 1+2 DC surge protector 1-pole - pluggable

CITEL

DS71R-48DC



- ↳ 2-poles surge protector 48 Vdc
- ↳ Type 1 and Type 2
- ↳ In 30 kA / I_{max} 70 kA
- ↳ Remote signaling
- ↳ I_{imp} 7 kA
- ↳ Pluggable Module
- ↳ IEC 61643-11 and EN61643-11 compliance



V: High-energy varistor
 Ft: Thermal fuse
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics	
SPD type	1+2
Network	48 Vdc
Nominal line voltage	Un 48 Vdc
Nominal DC voltage	Un-dc 48 Vdc
Max. DC operating voltage	Uc 65 Vdc
Residual Current <i>Leakage current to Ground</i>	I _{pe} < 0.1 mA
Follow current	I _f None
Nominal discharge current <i>15 x 8/20 μs impulses</i>	I _n 30 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max} 70 kA
Impulse current by pole <i>max. withstand 10/350μs by pole</i>	I _{imp} 7 kA
Connection mode(s)	+/-PE or -/PE
Protection level <i>@ I_n (8/20μs)</i>	U _p 300 V
Mechanical Characteristics	
Technology	MOV
SPD configuration	Single phase
Connection to Network	By screw terminals: 4-25mm ²
Format	Plug-in modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	T _u -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from DC network
Disconnection indicator	1 mechanical indicator
Spare module(s)	DSM70R-48DC
Remote signaling of disconnection	DS71RS-48DC option : output on changeover contact
Dimensions	See diagram
Disconnectors	
Thermal disconnector	Internal
Back-up protection device	100 A min. - 125 A max. - Fuses type gG
Standards	
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Part number	
322101	

