





Type 2 AC surge protector - 3-phase

CITEL

DAC50-30-530



- ▷ Type 2 AC surge protector
- ▷ In: 20 kA
- ▷ Imax: 50 kA
- ▷ Pluggable module for each phase
- ▷ Remote signaling option
- ▷ EN 61643-11, IEC 61643-11 and UL1449 ed.5 certified



V: High-energy varistor
 Ft: Thermal fuse
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics

SPD type	2	
Network	480 V 3-phase	
AC system	TNC-IT	
Max. AC operating voltage	Uc	530 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	700 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	920 Vac disconnection
Residual Current Leakage current to Ground	Ipe	< 1 mA
Follow current	If	None
Nominal discharge current 15 x 8/20 μs impulses	In	20 kA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	50 kA
Total Maximum discharge current max. total withstand @ 8/20 μs	Imax Total	150 kA
Protection mode(s)	L/PE	
Protection level L/PE @ In (8/20μs)	Up L/PE	2.4 kV
Residual voltage L/PE at 5 kA @ 5 kA (8/20μs)	Up-5kA	2 kV
Admissible short-circuit current	Iscsr	50 000 A

Mechanical Characteristics

Technology	MOV	
SPD configuration	3-phase	
Connection to Network	By screw terminals: 2.5-25mm ² (35mm ² rigid)	
Format	Plug-in modular box	
Mounting	Symmetrical rail 35 mm (EN 60715)	
Housing material	Thermoplastic UL94 V-0	
Operating temperature	Tu	-40/+85°C
Protection rating	IP20	
Failsafe mode	Disconnection from AC network	
Disconnection indicator	1 mechanical indicator by pole - Red/Green	
Spare module(s)	MDAC50-530	
Remote signaling of disconnection	option DAC50S-30-530 : output on changeover contact	
Wiring for remote signaling	1.5 mm ² max.	
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)	
Dimensions	See diagram - 3 TE (EN43880)	
Weight	0.348 kg	

Disconnectors

Thermal disconnector	Internal	
Installation ground fault breaker	Type 'S' or delayed	
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG	

Standards

Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5	
Certification	ÖVE / UL	

Part number

821110513

