




# Type 1+2 AC surge protector - 1-pole

# CITEL

## DAC1-13VG-10-275



- ↳ Type 1 + 2 + 3 AC surge protector
- ↳ VG Technology
- ↳  $I_n$  : 20 kA
- ↳  $I_{imp}$  : 12.5 kA on 10/350 $\mu$ s impulse
- ↳ No leakage current
- ↳ Pluggable module for each phase
- ↳ Remote signaling (option)
- ↳ Optimized to TOV
- ↳ EN 61643-11, IEC 61643-11 certified
- ↳ UL1449 ed.5 compliance



Electrical Characteristics		
SPD type		1+2+3
Max. AC operating voltage	Uc	275 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac withstand
Residual Current Leakage current to Ground	Ipe	None
Follow current	If	None
Nominal discharge current 15 x 8/20 $\mu$ s impulses	$I_n$	20 kA
Max. discharge current max. withstand @ 8/20 $\mu$ s by pole	$I_{max}$	50 kA
Impulse current by pole max. withstand 10/350 $\mu$ s by pole	$I_{imp}$	12.5 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50 $\mu$ s - 8/20 $\mu$ s	Uoc	6 kV
Specific energy by pole max. withstand 10/350 $\mu$ s	W/R	40 kJ/ohm
Protection level @ $I_n$ (8/20 $\mu$ s) and @ 6 kV (1.2/50 $\mu$ s)	Up	1.5 kV
Residual voltage at 5 kA @ 5 kA (8/20 $\mu$ s)	Up-5kA	0.7 kV
Admissible short-circuit current	Iscrc	50 000 A
Mechanical Characteristics		
Technology		VG Technology (MOV+GSG)
SPD configuration		Single phase
Connection to Network		By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator - Red/Green
Spare module(s)		MDAC1-13VG-275
Remote signaling of disconnection		option DAC1-13VGS-10-275: output on changeover contact
Wiring for remote signaling		1.5 mm <sup>2</sup> max.
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions		See diagram - 1TE (EN43880)
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		315 A max. - Fuses Type gG / or SFD1-25S
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification		KEMA
Part number		
821730211		

