





Type 2 AC surge protector - 3-phase

CITEL

DAC50VG-30-320



- Type 2 + 3 AC surge protector
- VG Technology
- In: 20 kA
- No leakage current
- Pluggable module for each phase
- Remote signaling (option)
- Optimized to TOV
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance



V: High-energy varistor
 Ft: Thermal fuse
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics

| | | |
|----------------------------------------------------------------------------------------------------------|------------|-------------------|
| SPD type | | 2+3 |
| Network | | 230/400 V 3-phase |
| AC system | | TNC |
| Max. AC operating voltage | Uc | 320 Vac |
| Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection | UT | 335 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection | UT | 440 Vac withstand |
| Residual Current Leakage current to Ground | Ipe | None |
| Follow current | If | None |
| Nominal discharge current 15 x 8/20 μs impulses | In | 20 kA |
| Max. discharge current max. withstand @ 8/20 μs by pole | Imax | 50 kA |
| Total Maximum discharge current max. total withstand @ 8/20 μs | Imax Total | 150 kA |
| Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs | Uoc | 6 kV |
| Connection mode(s) | | L/PE |
| Protection level L/PE @ In (8/20μs) | Up L/PE | 1.5 kV |
| Residual voltage L/PE at 5 kA @ 5 kA (8/20μs) | Up-5kA | 0.9 kV |
| Admissible short-circuit current | Iscrr | 50 000 A |

Mechanical Characteristics

| | | |
|-----------------------------------|----|---------------------------------------------------------------------|
| Technology | | VG Technology (MOV+GSG) |
| SPD configuration | | 3-phase |
| Connection to Network | | By screw terminals: 2.5-25mm ² (35mm ² rigid) |
| Format | | Plug-in modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from AC network |
| Disconnection indicator | | 1 mechanical indicator by pole - Red/Green |
| Spare module(s) | | MDAC50VG-320 |
| Remote signaling of disconnection | | option DAC50VGS-30-320 : output on changeover contact |
| Dimensions | | See diagram - 3 TE (EN43880) |
| Weight | | 0.289 kg |

Disconnectors

| | | |
|-----------------------------------|--|----------------------------------------|
| Thermal disconnector | | Internal |
| Installation ground fault breaker | | Type 'S' or delayed |
| Back-up protection device | | 50 A min. - 160 A max. - Fuses Type gG |

Standards

| | | |
|----------------------|--|------------------------------------------|
| Standards compliance | | IEC 61643-11 / EN 61643-11 / UL1449 ed.5 |
| Certification | | KEMA |

Part number

821130313

