




CITEL

1-pole Type 1 and Type 2 SPD for 48 Vdc

DDC30-10-65



- ↳ Surge protector for DC supplies 1-pole
- ↳ Type 1 + 2
- ↳ In: 15 kA / I_{max}: 30 kA
- ↳ I_{imp}: 4kA
- ↳ Pluggable module
- ↳ Remote signaling (option)
- ↳ prIEC 61643-41 compliance



Electrical Characteristics	
SPD type	1+2
Nominal DC voltage	Un-dc 48 Vdc
Max. AC operating voltage	Uc 50 Vac
Max. DC operating voltage	Uc 65 Vdc
Residual Current <i>Leakage current to Ground</i>	I _{pe} < 0.1 mA
Follow current	I _f None
Nominal discharge current <i>15 x 8/20 μs impulses</i>	I _n 15 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max} 30 kA
Impulse current by pole <i>max. withstand 10/350μs by pole</i>	I _{imp} 4 kA
Total lightning current <i>max. total withstand @ 10/350μs</i>	I _{total} 60 kA
Connection mode(s)	+/-PE or -/PE
Protection level +/-PE (-/PE) <i>@ I_n (8/20μs)</i>	U _p 300 V / -
Admissible short-circuit current	I _{sc} 50 000 A
Mechanical Characteristics	
Technology	MOV
SPD configuration	Single phase
Connection to Network	Screw terminals: 2.5-25mm ² +/- 1.5-10mm ²
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	T _u -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from AC network
Disconnection indicator	1 mechanical indicator - Red/Green
Spare module(s)	MDDC30-65
Remote signaling of disconnection	Option DDC30S-10-65: output on changeover contact
Wiring for remote signaling	1.5 mm ² max.
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions	See diagram - 1TE (EN43880)
Weight	0.094 kg
Disconnectors	
Thermal disconnector	Internal
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG
Standards	
Standards compliance	prIEC 61643-41
Part number	
828110111	

