



DAC40CS-20-150



- Compact Surge protector, 2-pole Type 2 or 3
- Conductivity per pole: $I_n = 20 \text{ kA}$; $I_{max} = 40 \text{ kA}$
- Common protection mode
- Safe disconnect device
- Transverse / longitudinal voltage protection
- Energetically coordinated
- Pluggable protection module
- Remote signalling
- IEC 61643-11 / EN 61643-11 certified
- UL1449 ed.5 compliance



	Electrical Characteristics																																																													
 V: High-energy varistor Ft: Thermal fuse C: Remote signal contact t*: Thermal disconnection system MI: Disconnection indicator		<table> <tr> <td>SPD type</td><td></td><td>2</td></tr> <tr> <td>Network</td><td></td><td>120 V single-phase</td></tr> <tr> <td>AC system</td><td></td><td>TN</td></tr> <tr> <td>Nominal line voltage</td><td>U_n</td><td>120 Vac</td></tr> <tr> <td>Max. AC operating voltage</td><td>U_c</td><td>150 Vac</td></tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>180 Vac withstand</td></tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>230 Vac disconnection</td></tr> <tr> <td>Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection</td><td>UT</td><td>1200 V/300A/200 ms withstand</td></tr> <tr> <td>Residual Current Leakage current to Ground</td><td>I_{pe}</td><td>< 1 mA</td></tr> <tr> <td>Follow current</td><td>I_f</td><td>None</td></tr> <tr> <td>Nominal discharge current 15 x 8/20 μs impulses</td><td>I_n</td><td>20 kA</td></tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>40 kA</td></tr> <tr> <td>Total Maximum discharge current max. total withstand @ 8/20 μs</td><td>I_{max} Total</td><td>40 kA</td></tr> <tr> <td>Connection mode(s)</td><td></td><td>L/N and N/PE</td></tr> <tr> <td>Protection mode(s)</td><td></td><td>L/PE and N/PE</td></tr> <tr> <td>Residual voltage at 5 kA @ 5 kA (8/20μs)</td><td>Up-5kA</td><td>0.6 kV</td></tr> <tr> <td>Protection level L/N @ I_n (8/20μs)</td><td>Up L/N</td><td>0.9 kV</td></tr> <tr> <td>Protection level N/PE @ I_n (8/20μs)</td><td>Up N/PE</td><td>0.9 kV</td></tr> <tr> <td>Protection level L/PE @ I_n (8/20μs)</td><td>Up L/PE</td><td>1.2 kV</td></tr> <tr> <td>Admissible short-circuit current</td><td>I_{scrr}</td><td>10 000 A</td></tr> </table>	SPD type		2	Network		120 V single-phase	AC system		TN	Nominal line voltage	U_n	120 Vac	Max. AC operating voltage	U_c	150 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	180 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	230 Vac disconnection	Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms withstand	Residual Current Leakage current to Ground	I_{pe}	< 1 mA	Follow current	I_f	None	Nominal discharge current 15 x 8/20 μ s impulses	I_n	20 kA	Max. discharge current max. withstand @ 8/20 μ s by pole	I_{max}	40 kA	Total Maximum discharge current max. total withstand @ 8/20 μ s	I_{max} Total	40 kA	Connection mode(s)		L/N and N/PE	Protection mode(s)		L/PE and N/PE	Residual voltage at 5 kA @ 5 kA (8/20 μ s)	Up-5kA	0.6 kV	Protection level L/N @ I_n (8/20 μ s)	Up L/N	0.9 kV	Protection level N/PE @ I_n (8/20 μ s)	Up N/PE	0.9 kV	Protection level L/PE @ I_n (8/20 μ s)	Up L/PE	1.2 kV	Admissible short-circuit current	I_{scrr}	10 000 A
SPD type		2																																																												
Network		120 V single-phase																																																												
AC system		TN																																																												
Nominal line voltage	U_n	120 Vac																																																												
Max. AC operating voltage	U_c	150 Vac																																																												
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	180 Vac withstand																																																												
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	230 Vac disconnection																																																												
Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms withstand																																																												
Residual Current Leakage current to Ground	I_{pe}	< 1 mA																																																												
Follow current	I_f	None																																																												
Nominal discharge current 15 x 8/20 μ s impulses	I_n	20 kA																																																												
Max. discharge current max. withstand @ 8/20 μ s by pole	I_{max}	40 kA																																																												
Total Maximum discharge current max. total withstand @ 8/20 μ s	I_{max} Total	40 kA																																																												
Connection mode(s)		L/N and N/PE																																																												
Protection mode(s)		L/PE and N/PE																																																												
Residual voltage at 5 kA @ 5 kA (8/20 μ s)	Up-5kA	0.6 kV																																																												
Protection level L/N @ I_n (8/20 μ s)	Up L/N	0.9 kV																																																												
Protection level N/PE @ I_n (8/20 μ s)	Up N/PE	0.9 kV																																																												
Protection level L/PE @ I_n (8/20 μ s)	Up L/PE	1.2 kV																																																												
Admissible short-circuit current	I_{scrr}	10 000 A																																																												
	Mechanical Characteristics																																																													
		<table> <tr> <td>Technology</td><td></td><td>MOV</td></tr> <tr> <td>SPD configuration</td><td></td><td>Single phase</td></tr> <tr> <td>Connection to Network</td><td></td><td>By screw terminals: L/N = 1.5-10mm² (16mm² rigid) or PE = 2.5-25mm² (35mm² rigid)</td></tr> <tr> <td>Format</td><td></td><td>Plug-in modular box</td></tr> <tr> <td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr> <td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr> <td>Operating temperature</td><td>T_u</td><td>-40/+85°C</td></tr> <tr> <td>Protection rating</td><td></td><td>IP20</td></tr> <tr> <td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr> <td>Disconnection indicator</td><td></td><td>1 mechanical indicator - Red/Green</td></tr> <tr> <td>Spare module(s)</td><td></td><td>MDAC40C-20-150</td></tr> <tr> <td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr> <td>Wiring for remote signaling</td><td></td><td>1.5 mm² max.</td></tr> <tr> <td>Max. Voltage/Current for remote signaling</td><td></td><td>250 V / 0.5 A (AC) / 30 V / 3 A (DC)</td></tr> <tr> <td>Dimensions</td><td></td><td>See diagram - 1TE (EN43880)</td></tr> <tr> <td>Weight</td><td></td><td>0.175 kg</td></tr> </table>	Technology		MOV	SPD configuration		Single phase	Connection to Network		By screw terminals: L/N = 1.5-10mm ² (16mm ² rigid) or PE = 2.5-25mm ² (35mm ² rigid)	Format		Plug-in modular box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	T_u	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator - Red/Green	Spare module(s)		MDAC40C-20-150	Remote signaling of disconnection		Output on changeover contact	Wiring for remote signaling		1.5 mm ² max.	Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	Dimensions		See diagram - 1TE (EN43880)	Weight		0.175 kg												
Technology		MOV																																																												
SPD configuration		Single phase																																																												
Connection to Network		By screw terminals: L/N = 1.5-10mm ² (16mm ² rigid) or PE = 2.5-25mm ² (35mm ² rigid)																																																												
Format		Plug-in modular box																																																												
Mounting		Symmetrical rail 35 mm (EN 60715)																																																												
Housing material		Thermoplastic UL94 V-0																																																												
Operating temperature	T_u	-40/+85°C																																																												
Protection rating		IP20																																																												
Failsafe mode		Disconnection from AC network																																																												
Disconnection indicator		1 mechanical indicator - Red/Green																																																												
Spare module(s)		MDAC40C-20-150																																																												
Remote signaling of disconnection		Output on changeover contact																																																												
Wiring for remote signaling		1.5 mm ² max.																																																												
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																																												
Dimensions		See diagram - 1TE (EN43880)																																																												
Weight		0.175 kg																																																												
	Disconnectors																																																													
		<table> <tr> <td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr> <td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr> <td>Back-up protection device</td><td></td><td>50 A min. - 125 A max. - Fuses Type gG</td></tr> </table>	Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		50 A min. - 125 A max. - Fuses Type gG																																																			
Thermal disconnector		Internal																																																												
Installation ground fault breaker		Type 'S' or delayed																																																												
Back-up protection device		50 A min. - 125 A max. - Fuses Type gG																																																												
	Standards																																																													
		<table> <tr> <td>Standards compliance</td><td></td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> <tr> <td>Certification</td><td></td><td>KEMA</td></tr> </table>	Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5	Certification		KEMA																																																						
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																												
Certification		KEMA																																																												



Compact 1-phase Type 2 surge protector - 150 V -Pluggable

DAC40CS-20-150

Part number
821510121

