



CITEL

Type 2 PV Surge Protector for PCB mounting

PPV25S-10-900



- Type 2 surge protector for Photovoltaic
- PCB mounting
- I_{max}: 25 kA
- Remote signaling
- EN 50539-11 and IEC 61643-31 compliance*



	Electrical Characteristics																																								
<p>V: High-energy varistor Ft: Thermal fuse C: Remote signal contact t°: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>2</td></tr> <tr><td>Max. PV operating voltage</td><td>U_{cpv}</td><td>900 Vdc</td></tr> <tr><td>Max. PV operating voltage (star mounting)</td><td>U_{cpv}</td><td>1800 Vdc</td></tr> <tr><td>PV Permanent Operating current</td><td>I_{cpv}</td><td>< 0.1 mA</td></tr> <tr><td>Current consumption at U_{cpv}</td><td></td><td></td></tr> <tr><td>Nominal discharge current</td><td>I_n</td><td>10 kA</td></tr> <tr><td>Max. discharge current</td><td>I_{max}</td><td>25 kA</td></tr> <tr><td>max. withstand @ 8/20 μs by pole</td><td></td><td></td></tr> <tr><td>Current withstand short circuit PV</td><td>I_{scpv}</td><td>15 000 A</td></tr> <tr><td>Protection level</td><td>U_p</td><td>2.8 kV</td></tr> <tr><td>@ I_n (8/20μs)</td><td></td><td></td></tr> <tr><td>Protection level (star mounting)</td><td>U_p</td><td>5.6 kV</td></tr> <tr><td>(+/-) / (+/PE or -/PE) @ I_n (8/20μs)</td><td></td><td></td></tr> </table>		SPD type		2	Max. PV operating voltage	U _{cpv}	900 Vdc	Max. PV operating voltage (star mounting)	U _{cpv}	1800 Vdc	PV Permanent Operating current	I _{cpv}	< 0.1 mA	Current consumption at U _{cpv}			Nominal discharge current	I _n	10 kA	Max. discharge current	I _{max}	25 kA	max. withstand @ 8/20 μs by pole			Current withstand short circuit PV	I _{scpv}	15 000 A	Protection level	U _p	2.8 kV	@ I _n (8/20μs)			Protection level (star mounting)	U _p	5.6 kV	(+/-) / (+/PE or -/PE) @ I _n (8/20μs)		
SPD type		2																																							
Max. PV operating voltage	U _{cpv}	900 Vdc																																							
Max. PV operating voltage (star mounting)	U _{cpv}	1800 Vdc																																							
PV Permanent Operating current	I _{cpv}	< 0.1 mA																																							
Current consumption at U _{cpv}																																									
Nominal discharge current	I _n	10 kA																																							
Max. discharge current	I _{max}	25 kA																																							
max. withstand @ 8/20 μs by pole																																									
Current withstand short circuit PV	I _{scpv}	15 000 A																																							
Protection level	U _p	2.8 kV																																							
@ I _n (8/20μs)																																									
Protection level (star mounting)	U _p	5.6 kV																																							
(+/-) / (+/PE or -/PE) @ I _n (8/20μs)																																									
Mechanical Characteristics																																									
<table border="1"> <tr><td>Technology</td><td></td><td>MOV</td></tr> <tr><td>Connection to Network</td><td></td><td>Through soldering pins</td></tr> <tr><td>Mounting</td><td></td><td>On Printed Circuit Board</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>T_u</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.058 kg</td></tr> </table>			Technology		MOV	Connection to Network		Through soldering pins	Mounting		On Printed Circuit Board	Housing material		Thermoplastic UL94 V-0	Operating temperature	T _u	-40/+85°C	Protection rating		IP20	Disconnection indicator		1 mechanical indicator	Remote signaling of disconnection		Output on changeover contact	Dimensions		See diagram	Weight		0.058 kg									
Technology		MOV																																							
Connection to Network		Through soldering pins																																							
Mounting		On Printed Circuit Board																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating temperature	T _u	-40/+85°C																																							
Protection rating		IP20																																							
Disconnection indicator		1 mechanical indicator																																							
Remote signaling of disconnection		Output on changeover contact																																							
Dimensions		See diagram																																							
Weight		0.058 kg																																							
Disconnectors																																									
<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Back-up protection device</td><td></td><td>Without</td></tr> </table>			Thermal disconnector		Internal	Back-up protection device		Without																																	
Thermal disconnector		Internal																																							
Back-up protection device		Without																																							
Standards																																									
<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-31 / EN 50539-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.</td></tr> </table>			Standards compliance		IEC 61643-31 / EN 50539-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.																																				
Standards compliance		IEC 61643-31 / EN 50539-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.																																							
Part number																																									
8721206																																									

