



Compact single-phase type 2 (or 3) surge protector - Monobloc

CITEL

DACN10-L21YG-275



- Cost effective single-phase surge protector
- Type 2+3 monobloc compact
- In/Imax: 5 kA/10 kA
- Max. load current: 16A
- Disconnection + AC line cut
- 2-port configuration (series mounting)
- Remote signaling
- EN 61643-11, IEC 61643-11 compliance



	Electrical Characteristics																																														
<p>V: High-energy varistor GSG: Specific Gas Tube LED: Disconnection indicator Ft: Thermal fuse t*: Thermal disconnection system</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>2+3</td></tr> <tr><td>Network</td><td></td><td>230 V single-phase</td></tr> <tr><td>AC system</td><td></td><td>TN</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>275 Vac</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>16 A</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>In</td><td>5 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>10 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td><td>Uoc</td><td>10 kV</td></tr> <tr><td>Protection level L/N @ In (8/20μs)</td><td>Up L/N</td><td>1.3 kV</td></tr> <tr><td>Protection level N/PE @ In (8/20μs)</td><td>Up N/PE</td><td>1.6 kV</td></tr> <tr><td>Protection level L/PE @ In (8/20μs)</td><td>Up L/PE</td><td>1.6 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>Iscsr</td><td>10 000 A</td></tr> </table>		SPD type		2+3	Network		230 V single-phase	AC system		TN	Max. AC operating voltage	Uc	275 Vac	Max. load current @25°C	IL	16 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Residual Current Leakage current to Ground	Ipe	None	Nominal discharge current 15 x 8/20 μs impulses	In	5 kA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	10 kV	Protection level L/N @ In (8/20μs)	Up L/N	1.3 kV	Protection level N/PE @ In (8/20μs)	Up N/PE	1.6 kV	Protection level L/PE @ In (8/20μs)	Up L/PE	1.6 kV	Admissible short-circuit current	Iscsr	10 000 A
SPD type		2+3																																													
Network		230 V single-phase																																													
AC system		TN																																													
Max. AC operating voltage	Uc	275 Vac																																													
Max. load current @25°C	IL	16 A																																													
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																													
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																													
Residual Current Leakage current to Ground	Ipe	None																																													
Nominal discharge current 15 x 8/20 μs impulses	In	5 kA																																													
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA																																													
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	10 kV																																													
Protection level L/N @ In (8/20μs)	Up L/N	1.3 kV																																													
Protection level N/PE @ In (8/20μs)	Up N/PE	1.6 kV																																													
Protection level L/PE @ In (8/20μs)	Up L/PE	1.6 kV																																													
Admissible short-circuit current	Iscsr	10 000 A																																													
	Mechanical Characteristics																																														
	SPD configuration	Single phase																																													
	Connection to Network	By screw terminals: 1.5-10mm ²																																													
	Mounting	Symmetrical rail 35 mm (EN 60715)																																													
	Housing material	Thermoplastic UL94 V-0																																													
	Operating temperature	Tu -40/+85°C																																													
	Protection rating	IP20																																													
	Failsafe mode	Disconnection and AC line cut-off																																													
	Disconnection indicator	Green LED OFF																																													
	Remote signaling of disconnection	option DACN10S-L21YG-275																																													
	Dimensions	See diagram - 1TE (EN43880)																																													
	Weight	0.086 kg																																													
	Disconnectors																																														
	Thermal disconnector	Internal																																													
	Installation ground fault breaker	Type 'S' or delayed																																													
	Back-up protection device	Fuses type gG - 25A																																													
	Standards																																														
	Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																													
	Part number	70115021																																													

