



DACN10S-20-440



- Cost effective single-phase surge protector
- Type 2 or 3 monobloc compact
- In/Imax: 5 kA/10 kA
- Max. load current: 25A
- 2-port configuration (series mounting)
- Remote signaling
- EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance



	Electrical Characteristics	
	SPD type	2 (or 3)
 V: High-energy varistor GSG: Specific Gas Tube LED: Disconnection indicator Ft: Thermal fuse t*: Thermal disconnection system	Network	230 V single-phase
	AC system	IT-TN
	Max. AC operating voltage	Uc 440 Vac
	Max. load current	IL 25 A
	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 580 Vac withstand
	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 770 Vac disconnection
	Residual Current Leakage current to Ground	Ipe < 1 mA
	Nominal discharge current 15 x 8/20 μ s impulses	In 5 kA
	Max. discharge current max. withstand @ 8/20 μ s by pole	Imax 10 kA
	Total Maximum discharge current max. total withstand @ 8/20 μ s	Imax Total 20 kA
	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50 μ s - 8/20 μ s	Uoc 10 kV
	Protection level N/PE @ In (8/20 μ s)	Up N/PE 1.6 kV
	Protection level L/PE @ In (8/20 μ s)	Up L/PE 1.6 kV
	Admissible short-circuit current	Iscrr 10 000 A
Mechanical Characteristics		
	SPD configuration	Single phase
	Connection to Network	By screw terminals: 1.5-10mm ²
	Mounting	Symmetrical rail 35 mm (EN 60715)
	Housing material	Thermoplastic UL94 V-0
	Operating temperature	Tu -40/+85°C
	Protection rating	IP20
	Failsafe mode	Disconnection from AC network
	Disconnection indicator	Green LED OFF
	Remote signaling of disconnection	output on NC contact
	Wiring for remote signaling	1.5 mm ² max.
	Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 2 A (DC)
	Dimensions	See diagram - 1TE (EN43880)
	Weight	0.092 kg
Disconnectors		
	Thermal disconnector	Internal
	Installation ground fault breaker	Type 'S' or delayed
	Back-up protection device	Fuses type gG - 25A
Standards		
	Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
	Part number	70113032