



# 1-pair DIN rail plug-in Data surge protector

# CITEL

## DLAS1-48D3/R



- 1-pair Pluggable SPD for dataline
- Visual indicator in failsafe behaviour
- Without line cut-off
- Line voltage 48 Vdc
- Din rail mounting, spring contact
- IEC/EN 61643-21 and UL497A compliance



	<b>Electrical Characteristics</b>																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D : Clamping diode Vi : Indicator</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RNIS-T0, 48 V line</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>53 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 µs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection level @ In (8/20 µs)</td> <td>Up L/L</td> <td>70 V</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td> <td>In L/PE</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>&lt; 4.7 Ohm</td> </tr> </table>		Network		RNIS-T0, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Line inductance		No	Protection level @ In (8/20 µs)	Up L/L	70 V	Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		< 4.7 Ohm
Network		RNIS-T0, 48 V line																																				
Nominal line voltage	Un	48 V																																				
Max. DC operating voltage	Uc	53 Vdc																																				
Max. frequency	f max.	> 3 MHz																																				
Max. load current @25°C	IL	300 mA																																				
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																				
Line inductance		No																																				
Protection level @ In (8/20 µs)	Up L/L	70 V																																				
Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA																																				
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																				
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA																																				
Line resistance		< 4.7 Ohm																																				
	<b>Mechanical Characteristics</b>																																					
	<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode+PTC (thermal resistor) + Resistor</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">By spring contact terminal: 0.5-4 mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Opening line - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Visual indicator is red</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLAS1M-48D3</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram</td> </tr> </table>		Technology	GDT+Clamping diode+PTC (thermal resistor) + Resistor		SPD configuration	1-pair+shielded		Connection to Network	By spring contact terminal: 0.5-4 mm <sup>2</sup>		Format	Plug-in DIN box		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating temperature	Tu	-40/+85°C	Protection rating	IP20		Failsafe mode	Opening line - transmission cut-off - fault mode 2		Disconnection indicator	Visual indicator is red		Spare module(s)	DLAS1M-48D3		Dimensions	See diagram	
Technology	GDT+Clamping diode+PTC (thermal resistor) + Resistor																																					
SPD configuration	1-pair+shielded																																					
Connection to Network	By spring contact terminal: 0.5-4 mm <sup>2</sup>																																					
Format	Plug-in DIN box																																					
Mounting	Symmetrical rail 35 mm (EN 60715)																																					
Housing material	Thermoplastic UL94 V-0																																					
Operating temperature	Tu	-40/+85°C																																				
Protection rating	IP20																																					
Failsafe mode	Opening line - transmission cut-off - fault mode 2																																					
Disconnection indicator	Visual indicator is red																																					
Spare module(s)	DLAS1M-48D3																																					
Dimensions	See diagram																																					
	<b>Standards</b>																																					
	<table border="1"> <tr> <td>Standards compliance</td> <td colspan="2">IEC 61643-21 / EN 61643-21 / UL497A</td> </tr> </table>		Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																		
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																					
	<b>Part number</b>																																					
	<table border="1"> <tr> <td>6415044</td> <td colspan="2"></td> </tr> </table>		6415044																																			
6415044																																						

