



CITEL

1-pair DIN rail plug-in Data surge protector

DLAS1-12D3/R



- 1-pair Pluggable SPD for dataline
- Visual indicator in failsafe behaviour
- Without line cut-off
- Line voltage 12 Vdc
- Din rail mounting, spring contact
- IEC/EN 61643-21 and UL497A compliance



	Electrical Characteristics																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D: Clamping diode Vi: Indicator</p>	<table border="1"> <tr><td>Network</td><td></td><td>RS232 - RS485</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>12 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>15 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance</td><td></td><td>No</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/L</td><td>30 V</td></tr> <tr><td>Impulse current 2 x 10/350μs Test - D1 Category</td><td>Iimp</td><td>5 kA</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>In L/L</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category</td><td>In L/PE</td><td>5 kA</td></tr> <tr><td>Line resistance</td><td></td><td>< 4.7 Ohm</td></tr> </table>		Network		RS232 - RS485	Nominal line voltage	Un	12 V	Max. DC operating voltage	Uc	15 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection level @ In (8/20 μs)	Up L/L	30 V	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		< 4.7 Ohm
Network		RS232 - RS485																																				
Nominal line voltage	Un	12 V																																				
Max. DC operating voltage	Uc	15 Vdc																																				
Max. frequency	f max.	> 3 MHz																																				
Max. load current @25°C	IL	300 mA																																				
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																				
Line inductance		No																																				
Protection level @ In (8/20 μs)	Up L/L	30 V																																				
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																				
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																				
Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA																																				
Line resistance		< 4.7 Ohm																																				
ELEC																																						
Nominal line voltage		Un 24 V																																				
Mechanical Characteristics																																						
Technology		GDT+Clamping diode+PTC (thermal resistor) + Resistor																																				
SPD configuration		1-pair+shielded																																				
Connection to Network		By spring contact terminal: 0.5-4 mm ²																																				
Format		Plug-in DIN box																																				
Mounting		Symmetrical rail 35 mm (EN 60715)																																				
Housing material		Thermoplastic UL94 V-0																																				
Operating temperature		Tu -40/+85°C																																				
Protection rating		IP20																																				
Failsafe mode		Opening line - transmission cut-off - fault mode 2																																				
Disconnection indicator		Visual indicator is red																																				
Spare module(s)		DLAS1M-12D3																																				
Dimensions		See diagram																																				
Standards																																						
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A																																				
Part number																																						
6415024																																						

