



DACF15-10-150



- Type 2 (or 3) AC surge protector
- Interne Disconnection device
- Low caliber of the internal connector = systematic coordination with upstream circuit breaker
- In : 5 kA
- I_{max} : 15 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance



	Electrical Characteristics																																														
 <p>V: High-energy varistor Ft: Thermal fuse F: Overcurrent protection (fuse) t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tbody> <tr><td>SPD type</td><td></td><td>2 (or 3)</td></tr> <tr><td>Max. AC operating voltage</td><td>U_c</td><td>150 Vac</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>180 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>230 Vac withstand</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>I_{pe}</td><td>< 1 mA</td></tr> <tr><td>Follow current</td><td>I_f</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>I_n</td><td>5 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>15 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td><td>U_{oc}</td><td>10 kV</td></tr> <tr><td>Protection level @ I_n (8/20μs)</td><td>U_p</td><td>0.6 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I_{scrr}</td><td>100 000 A</td></tr> </tbody> </table>		SPD type		2 (or 3)	Max. AC operating voltage	U _c	150 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	180 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	230 Vac withstand	Residual Current Leakage current to Ground	I _{pe}	< 1 mA	Follow current	I _f	None	Nominal discharge current 15 x 8/20 μs impulses	I _n	5 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	15 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U _{oc}	10 kV	Protection level @ I _n (8/20μs)	U _p	0.6 kV	Admissible short-circuit current	I _{scrr}	100 000 A												
SPD type		2 (or 3)																																													
Max. AC operating voltage	U _c	150 Vac																																													
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	180 Vac withstand																																													
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	230 Vac withstand																																													
Residual Current Leakage current to Ground	I _{pe}	< 1 mA																																													
Follow current	I _f	None																																													
Nominal discharge current 15 x 8/20 μs impulses	I _n	5 kA																																													
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	15 kA																																													
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U _{oc}	10 kV																																													
Protection level @ I _n (8/20μs)	U _p	0.6 kV																																													
Admissible short-circuit current	I _{scrr}	100 000 A																																													
Mechanical Characteristics																																															
<table border="1"> <tbody> <tr><td>Technology</td><td></td><td>MOV</td></tr> <tr><td>SPD configuration</td><td></td><td>Single phase</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 2.5-25mm² (35mm² rigid)</td></tr> <tr><td>Format</td><td></td><td>Plug-in modular box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>T_u</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator - Red/Green</td></tr> <tr><td>Spare module(s)</td><td></td><td>MDACF15-150</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>option DACF15S-10-150 : output on changeover contact</td></tr> <tr><td>Wiring for remote signaling</td><td></td><td>1.5 mm² max.</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram - 1TE (EN43880)</td></tr> <tr><td>Weight</td><td></td><td>0.106 kg</td></tr> </tbody> </table>			Technology		MOV	SPD configuration		Single phase	Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)	Format		Plug-in modular box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	T _u	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator - Red/Green	Spare module(s)		MDACF15-150	Remote signaling of disconnection		option DACF15S-10-150 : output on changeover contact	Wiring for remote signaling		1.5 mm ² max.	Dimensions		See diagram - 1TE (EN43880)	Weight		0.106 kg
Technology		MOV																																													
SPD configuration		Single phase																																													
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)																																													
Format		Plug-in modular box																																													
Mounting		Symmetrical rail 35 mm (EN 60715)																																													
Housing material		Thermoplastic UL94 V-0																																													
Operating temperature	T _u	-40/+85°C																																													
Protection rating		IP20																																													
Failsafe mode		Disconnection from AC network																																													
Disconnection indicator		1 mechanical indicator - Red/Green																																													
Spare module(s)		MDACF15-150																																													
Remote signaling of disconnection		option DACF15S-10-150 : output on changeover contact																																													
Wiring for remote signaling		1.5 mm ² max.																																													
Dimensions		See diagram - 1TE (EN43880)																																													
Weight		0.106 kg																																													
Disconnectors																																															
<table border="1"> <tbody> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr><td>Back-up protection device</td><td></td><td>internal (equivalent AC rating : 25 A, gG Type)</td></tr> </tbody> </table>			Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		internal (equivalent AC rating : 25 A, gG Type)																																				
Thermal disconnector		Internal																																													
Installation ground fault breaker		Type 'S' or delayed																																													
Back-up protection device		internal (equivalent AC rating : 25 A, gG Type)																																													
Standards																																															
<table border="1"> <tbody> <tr><td>Standards compliance</td><td></td><td>IEC 61643-11 / EN 61643-11</td></tr> </tbody> </table>			Standards compliance		IEC 61643-11 / EN 61643-11																																										
Standards compliance		IEC 61643-11 / EN 61643-11																																													
Part number																																															
821310111																																															