



# Type 1+2+3 AC surge protector - Single phase

# CITEL

## DS252VG-120/G



- Type 1+2+3 unipolar surge protector
- 25 kA on 10/350µs impulse
- Low voltage Up
- Internal disconnection, status indicator and remote signaling
- Optimized to TOV
- IEC 61643-11 and UL1449 ed.5 compliance



	<b>Electrical Characteristics</b>																																																																									
<p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>1+2+3</td></tr> <tr><td>Network</td><td></td><td>120 V single-phase</td></tr> <tr><td>AC system</td><td></td><td>TT-TN</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>120 Vac</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>150 Vac</td></tr> <tr><td>Max. load current <i>if series connection</i></td><td>IL</td><td>100 A</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i></td><td>UT</td><td>180 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i></td><td>UT</td><td>230 Vac withstand</td></tr> <tr><td>Temporary Over Voltage N/PE (TOV HT) <i>Without disconnection or with safety disconnection</i></td><td>UT</td><td>1200 V/300A/200 ms withstand</td></tr> <tr><td>Residual Current <i>Leakage current to Ground</i></td><td>Ipe</td><td>None</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current <i>15 x 8/20 µs impulses</i></td><td>In</td><td>30 kA</td></tr> <tr><td>Max. discharge current <i>max. withstand @ 8/20 µs by pole</i></td><td>Imax</td><td>70 kA</td></tr> <tr><td>Impulse current by pole <i>max. withstand 10/350µs by pole</i></td><td>Iimp</td><td>25 kA</td></tr> <tr><td>Total lightning current <i>max. total withstand @ 10/350µs</i></td><td>Itotal</td><td>50 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50µs - 8/20µs</i></td><td>Uoc</td><td>20 kV</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>20 kV</td></tr> <tr><td>Specific energy by pole <i>max. withstand 10/350 µs</i></td><td>W/R</td><td>156 kJ/ohm</td></tr> <tr><td>Connection mode(s)</td><td></td><td>L/N and N/PE</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Residual voltage <i>@ In (8/20 µs)</i></td><td>Up-in</td><td>0.7 kV</td></tr> <tr><td>Protection level L/N <i>@ In (8/20µs)</i></td><td>Up L/N</td><td>1 kV</td></tr> <tr><td>Protection level N/PE <i>@ In (8/20µs)</i></td><td>Up N/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>Iscrr</td><td>50 000 A</td></tr> </table>		SPD type		1+2+3	Network		120 V single-phase	AC system		TT-TN	Nominal line voltage	Un	120 Vac	Max. AC operating voltage	Uc	150 Vac	Max. load current <i>if series connection</i>	IL	100 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i>	UT	180 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i>	UT	230 Vac withstand	Temporary Over Voltage N/PE (TOV HT) <i>Without disconnection or with safety disconnection</i>	UT	1200 V/300A/200 ms withstand	Residual Current <i>Leakage current to Ground</i>	Ipe	None	Follow current	If	None	Nominal discharge current <i>15 x 8/20 µs impulses</i>	In	30 kA	Max. discharge current <i>max. withstand @ 8/20 µs by pole</i>	Imax	70 kA	Impulse current by pole <i>max. withstand 10/350µs by pole</i>	Iimp	25 kA	Total lightning current <i>max. total withstand @ 10/350µs</i>	Itotal	50 kA	Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50µs - 8/20µs</i>	Uoc	20 kV	Withstand on overvoltages IEEE C62.41.1		20 kV	Specific energy by pole <i>max. withstand 10/350 µs</i>	W/R	156 kJ/ohm	Connection mode(s)		L/N and N/PE	Protection mode(s)		Common/Differential mode	Residual voltage <i>@ In (8/20 µs)</i>	Up-in	0.7 kV	Protection level L/N <i>@ In (8/20µs)</i>	Up L/N	1 kV	Protection level N/PE <i>@ In (8/20µs)</i>	Up N/PE	1.5 kV	Admissible short-circuit current	Iscrr	50 000 A
SPD type		1+2+3																																																																								
Network		120 V single-phase																																																																								
AC system		TT-TN																																																																								
Nominal line voltage	Un	120 Vac																																																																								
Max. AC operating voltage	Uc	150 Vac																																																																								
Max. load current <i>if series connection</i>	IL	100 A																																																																								
Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i>	UT	180 Vac withstand																																																																								
Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i>	UT	230 Vac withstand																																																																								
Temporary Over Voltage N/PE (TOV HT) <i>Without disconnection or with safety disconnection</i>	UT	1200 V/300A/200 ms withstand																																																																								
Residual Current <i>Leakage current to Ground</i>	Ipe	None																																																																								
Follow current	If	None																																																																								
Nominal discharge current <i>15 x 8/20 µs impulses</i>	In	30 kA																																																																								
Max. discharge current <i>max. withstand @ 8/20 µs by pole</i>	Imax	70 kA																																																																								
Impulse current by pole <i>max. withstand 10/350µs by pole</i>	Iimp	25 kA																																																																								
Total lightning current <i>max. total withstand @ 10/350µs</i>	Itotal	50 kA																																																																								
Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50µs - 8/20µs</i>	Uoc	20 kV																																																																								
Withstand on overvoltages IEEE C62.41.1		20 kV																																																																								
Specific energy by pole <i>max. withstand 10/350 µs</i>	W/R	156 kJ/ohm																																																																								
Connection mode(s)		L/N and N/PE																																																																								
Protection mode(s)		Common/Differential mode																																																																								
Residual voltage <i>@ In (8/20 µs)</i>	Up-in	0.7 kV																																																																								
Protection level L/N <i>@ In (8/20µs)</i>	Up L/N	1 kV																																																																								
Protection level N/PE <i>@ In (8/20µs)</i>	Up N/PE	1.5 kV																																																																								
Admissible short-circuit current	Iscrr	50 000 A																																																																								
<b>Mechanical Characteristics</b>																																																																										
<table border="1"> <tr><td>Technology</td><td></td><td>VG Technology (MOV+GSG)</td></tr> <tr><td>SPD configuration</td><td></td><td>Single phase</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 6-35mm<sup>2</sup> / by bus</td></tr> <tr><td>Format</td><td></td><td>1-pole modular box assembled</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator by pole</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.46 kg</td></tr> </table>			Technology		VG Technology (MOV+GSG)	SPD configuration		Single phase	Connection to Network		By screw terminals: 6-35mm <sup>2</sup> / by bus	Format		1-pole modular box assembled	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator by pole	Remote signaling of disconnection		Output on changeover contact	Dimensions		See diagram	Weight		0.46 kg																																	
Technology		VG Technology (MOV+GSG)																																																																								
SPD configuration		Single phase																																																																								
Connection to Network		By screw terminals: 6-35mm <sup>2</sup> / by bus																																																																								
Format		1-pole modular box assembled																																																																								
Mounting		Symmetrical rail 35 mm (EN 60715)																																																																								
Housing material		Thermoplastic UL94 V-0																																																																								
Operating temperature	Tu	-40/+85°C																																																																								
Protection rating		IP20																																																																								
Failsafe mode		Disconnection from AC network																																																																								
Disconnection indicator		1 mechanical indicator by pole																																																																								
Remote signaling of disconnection		Output on changeover contact																																																																								
Dimensions		See diagram																																																																								
Weight		0.46 kg																																																																								
<b>Disconnectors</b>																																																																										
<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr><td>Back-up protection device</td><td></td><td>SFD1-25S-11 / or Fuses Type gG 315 A</td></tr> </table>			Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		SFD1-25S-11 / or Fuses Type gG 315 A																																																															
Thermal disconnector		Internal																																																																								
Installation ground fault breaker		Type 'S' or delayed																																																																								
Back-up protection device		SFD1-25S-11 / or Fuses Type gG 315 A																																																																								
<b>Standards</b>																																																																										
<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> <tr><td>Certification</td><td></td><td>UL Recognized</td></tr> </table>			Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5	Certification		UL Recognized																																																																		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																																								
Certification		UL Recognized																																																																								

DS252VG-120/G

Part number

3960