


DDCN06S-21YG-65



- DC Power Type 2+3 SPD
- 2-port configuration (series mounting)
- Compact and Cost effective
- In/Imax: 2 kA/6 kA
- Max. load current: 25A
- Disconnection + AC line cut
- Remote signaling
- EN 61643-11, IEC 61643-11 compliance



V: High-energy varistor
GSG: Specific Gas Tube
LED: Disconnection indicator
Ft: Thermal fuse
t*: Thermal disconnection system
C: Remote signaling contact

Electrical Characteristics		
Nominal DC voltage	Un-dc	48 Vdc
Max. DC operating voltage	Uc	65 Vdc
Max. load current	IL	25 A
Residual Current	Ipe	None
Leakage current to Ground		
Nominal discharge current	In	2 kA
15 x 8/20 μ s impulses		
Max. discharge current	Imax	6 kA
max. withstand @ 8/20 μ s by pole		
Withstand on Combination waveform IEC 61643-11	Uoc	4 kV
Class III test: 1.2/50 μ s - 8/20 μ s		
Connection mode(s)		+/-/PE
Protection level +/-	Up	0.5 kV
@ In (8/20 μ s)		
Protection level +/-PE (-/PE)	Up	0.8 kV
@ In (8/20 μ s)		
Admissible short-circuit current	Iscrr	10 000 A
Mechanical Characteristics		
SPD configuration		Single phase
Connection to Network		By screw terminals: 1.5-10mm ²
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from DC network
Disconnection indicator		Green LED OFF
Remote signaling of disconnection		output on NC contact
Dimensions		See diagram - 1TE (EN43880)
Weight		0.089 kg
Disconnectors		
Thermal disconnector		Internal
Back-up protection device		Fuses type gG - 25A
Standards		
Standards compliance		IEC 61643-11 / prIEC 61643-41
Part number		
70134052		