




Type 2 AC surge protector - Re-inforced - pluggable

CITEL

DAC80-20-440



- Re-inforced Type 2 AC surge protector
- In : 40 kA
- Imax : 80 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance



Electrical Characteristics	
SPD type	2
Network	230 V single-phase
AC system	IT
Max. AC operating voltage	Uc 440 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 580 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 770 Vac disconnection
Residual Current Leakage current to Ground	Ipe < 1 mA
Follow current	If None
Nominal discharge current 15 x 8/20 μs impulses	In 40 kA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax 80 kA
Protection mode(s)	L/PE and N/PE
Protection level N/PE @ In (8/20μs)	Up N/PE 2 kV
Protection level L/PE @ In (8/20μs)	Up L/PE 2 kV
Admissible short-circuit current	Iscrr 50 000 A
Mechanical Characteristics	
Technology	MOV
Connection to Network	By screw terminals: 2.5-25mm ² (35mm ² rigid)
Format	Plug-in modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from AC network
Disconnection indicator	1 mechanical indicator by pole - Red/Green
Spare module(s)	MDAC80-440
Remote signaling of disconnection	option DAC80S-20-440 : output on changeover contact
Dimensions	See diagram - 2TE (EN43880)
Weight	0.257 kg
Disconnectors	
Thermal disconnector	Internal
Installation ground fault breaker	Type 'S' or delayed
Back-up protection device	Fuses Type gG - 125 A
Standards	
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification	KEMA
Part number	
821210412	

