



Type 2 AC surge protector - Re-inforced - pluggable

CITEL

DAC80S-30-440



- Re-inforced Type 2 AC surge protector
- In: 40 kA
- Imax: 80 kA
- Pluggable module for each phase
- Remote signaling
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance



	Electrical Characteristics		
	SPD type	2	
<p>V: High-energy varistor Ft: Thermal fuse C: Remote signal contact t*: Thermal disconnection system MI: Disconnection indicator</p>	Network	230/400 V 3-phase	
	AC system	IT	
	Max. AC operating voltage	Uc	440 Vac
	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand
	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac disconnection
	Residual Current Leakage current to Ground	Ipe	< 1 mA
	Follow current	If	None
	Nominal discharge current 15 x 8/20 μs impulses	In	40 kA
	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	80 kA
	Protection mode(s)		L/PE
Protection level L/PE @ In (8/20μs)	Up L/PE	2 kV	
Admissible short-circuit current	Iscrr	50 000 A	
Mechanical Characteristics			
Technology		MOV	
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)	
Format		Plug-in modular box	
Mounting		Symmetrical rail 35 mm (EN 60715)	
Housing material		Thermoplastic UL94 V-0	
Operating temperature	Tu	-40/+85°C	
Protection rating		IP20	
Failsafe mode		Disconnection from AC network	
Disconnection indicator		1 mechanical indicator by pole - Red/Green	
Spare module(s)		MDAC80-440	
Remote signaling of disconnection		Output on changeover contact	
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	
Dimensions		See diagram - 3 TE (EN43880)	
Weight		0.391 kg	
Disconnectors			
Thermal disconnector		Internal	
Installation ground fault breaker		Type 'S' or delayed	
Back-up protection device		Fuses Type gG - 125 A	
Standards			
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5	
Certification		KEMA	
Part number			
821210423			

