



Type 2+3 AC surge protector -3-pole - Monobloc

CITEL

DACN30VGS-30-1260



- Type 2 + 3 AC surge protector
- VG Technology
- In: 15 kA
- No leakage current
- Monobloc module for each phase
- Remote signaling
- Optimized to TOV
- EN 61643-11, IEC 61643-11 and UL1449 ed.5 compliance



	Electrical Characteristics																																											
<p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr> <td>SPD type</td> <td></td> <td>2+3</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>1140 Vac</td> </tr> <tr> <td>Max. AC operating voltage</td> <td>Uc</td> <td>1260 Vac</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td> <td>UT</td> <td>1650 Vac withstand</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td> <td>UT</td> <td>2200 Vac disconnection</td> </tr> <tr> <td>Residual Current Leakage current to Ground</td> <td>Ipe</td> <td>None</td> </tr> <tr> <td>Follow current</td> <td>If</td> <td>None</td> </tr> <tr> <td>Nominal discharge current 15 x 8/20 μs impulses</td> <td>In</td> <td>15 kA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I_{max}</td> <td>30 kA</td> </tr> <tr> <td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td> <td>Uoc</td> <td>6 kV</td> </tr> <tr> <td>Protection level @ In (8/20μs)</td> <td>Up</td> <td>4.0 kV</td> </tr> <tr> <td>Protection level @ In (8/20μs) and @ 6 kV (1.2/50 μs)</td> <td>Up</td> <td>5.0 kV</td> </tr> <tr> <td>Residual voltage at 5 kA @ 5 kA (8/20μs)</td> <td>Up-5kA</td> <td>3.2 kV</td> </tr> <tr> <td>Admissible short-circuit current</td> <td>I_{sc}</td> <td>25 000 A</td> </tr> </table>		SPD type		2+3	Nominal line voltage	Un	1140 Vac	Max. AC operating voltage	Uc	1260 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	1650 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	2200 Vac disconnection	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 μs impulses	In	15 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	30 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	6 kV	Protection level @ In (8/20μs)	Up	4.0 kV	Protection level @ In (8/20μs) and @ 6 kV (1.2/50 μs)	Up	5.0 kV	Residual voltage at 5 kA @ 5 kA (8/20μs)	Up-5kA	3.2 kV	Admissible short-circuit current	I _{sc}	25 000 A
SPD type		2+3																																										
Nominal line voltage	Un	1140 Vac																																										
Max. AC operating voltage	Uc	1260 Vac																																										
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	1650 Vac withstand																																										
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	2200 Vac disconnection																																										
Residual Current Leakage current to Ground	Ipe	None																																										
Follow current	If	None																																										
Nominal discharge current 15 x 8/20 μs impulses	In	15 kA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	30 kA																																										
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	6 kV																																										
Protection level @ In (8/20μs)	Up	4.0 kV																																										
Protection level @ In (8/20μs) and @ 6 kV (1.2/50 μs)	Up	5.0 kV																																										
Residual voltage at 5 kA @ 5 kA (8/20μs)	Up-5kA	3.2 kV																																										
Admissible short-circuit current	I _{sc}	25 000 A																																										
	Mechanical Characteristics																																											
	Technology VG Technology (MOV+GSG)																																											
	SPD configuration 3-phase																																											
	Connection to Network By screw terminals: 2.5-25mm ² (35mm ² rigid)																																											
	Format Monobloc modular box																																											
	Mounting Symmetrical rail 35 mm (EN 60715)																																											
	Housing material Thermoplastic UL94 V-0																																											
	Operating temperature Tu -40/+85°C																																											
	Protection rating IP20																																											
	Failsafe mode Disconnection from AC network																																											
	Disconnection indicator 1 mechanical indicator - Red/Green																																											
	Remote signaling of disconnection Output on changeover contact																																											
	Wiring for remote signaling 1.5 mm ² max.																																											
	Max. Voltage/Current for remote signaling 250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																											
	Dimensions See diagram - 6TE (EN43880)																																											
	Weight 0.749 kg																																											
	Disconnectors																																											
	Thermal disconnector Internal																																											
	Installation ground fault breaker Type 'S' or delayed																																											
	Back-up protection device Fuses type gG - 50 A																																											
	Standards																																											
	Standards compliance IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																											
	Part number																																											
	29423032																																											

