

MJ8-POE-IT



- POE++ compatible (IEEE 802.3bt)
- 10G compatible from 5m to 100m in the channel, using Cat-6A S/FTP cabling
- RJ45 Shielded connectors
- IEC 61643-21, EN 61643-21
- Indoor application: IP20 rating (NEMA 2)
- Plastic enclosure, UL94-V0
- Location and test categories: D1, C2, C3



Electrical Characteristics		
Network		POE-B and Gigabit Ethernet, High POE
Nominal line voltage	Un	5 Vdc/48 Vdc
Max. DC operating voltage	Uc	7.5 Vdc (1.2.3.6) - 60 Vdc (4.5.7.8)
Max. frequency	f max.	250 MHz
Max. data rate		10/100/1000 Mbps
Insertion loss		< 1 dB
Protection level @ In (8/20 μs)	Up L/L	20/70 V
Impulse current 2 x 10/350 μs Test - D1 Category	Iimp	500 A
Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	In L/PE	2000 A
Mechanical Characteristics		
Technology		GDT+Clamping diode
SPD configuration		8 wires+shielded
Connection to Network		RJ45 shielded connectors Female input/output
Format		Metallic box with connectors input/output
Mounting		Mounting flange, Screw lug, DIN Rail
Accessory(s) provided		DIN rail adapter, screw, screw nut, earthing plate, countersunk screw, cable shoe
Housing material		Aluminium
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit - transmission cut-off
Pinout		(1-2)(3-6)(4-5)(7-8)
Dimensions		See diagram
Weight		0.115 kg
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497 B / IEEE 802-3ab/3at
Certification		UL 497B
Part number		
581548		