



NEW CITEL PV SPD

- Type 2+3 surge protector for Photovoltaic
- CTC Technology
- VG Technology
- Discharge currents I_{max}/I_{total}: 40/60 kA (8/20μs)
- Common/Differential mode protection
- Remote signaling
- IEC 61643-31, EN 61643-31, EN 50539-11, UL1449 ed.5 compliance
- Certified EN 61643-31 and IEC 61643-31



	Electrical Characteristics																																																							
<p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Mechanical status indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>2+3</td></tr> <tr><td>Network</td><td></td><td>PV 1200 Vdc</td></tr> <tr><td>Nominal PV voltage</td><td>U_{ocstc}</td><td>1000 Vdc</td></tr> <tr><td>Max. PV operating voltage</td><td>U_{cpv}</td><td>1200 Vdc</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>I_{pe}</td><td>None</td></tr> <tr><td>PV Permanent Operating current Current consumption at U_{cpv}</td><td>I_{cpv}</td><td>None</td></tr> <tr><td>Follow current</td><td>I_f</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>I_n</td><td>20 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>40 kA</td></tr> <tr><td>Total Maximum discharge current max. total withstand @ 8/20 μs</td><td>I_{max} Total</td><td>60 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td><td>U_{oc}</td><td>6 kV</td></tr> <tr><td>Current withstand short circuit PV</td><td>I_{scpv}</td><td>15 000 A</td></tr> <tr><td>Connection mode(s)</td><td></td><td>+/-/PE</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level +/- @ I_n (8/20μs)</td><td>U_p</td><td>4.3 kV</td></tr> <tr><td>Protection level +/-PE (-/PE) @ I_n (8/20μs)</td><td>U_p</td><td>4.3 kV</td></tr> <tr><td>Protection level at 5 kA @ 5 kA (8/20μs)</td><td>U_p</td><td>3,5 kV</td></tr> <tr><td>Protection level at U_{oc} @ U_{oc} (1.2/50 μs)</td><td>U_p</td><td>3,1 kV</td></tr> </table>		SPD type		2+3	Network		PV 1200 Vdc	Nominal PV voltage	U _{ocstc}	1000 Vdc	Max. PV operating voltage	U _{cpv}	1200 Vdc	Residual Current Leakage current to Ground	I _{pe}	None	PV Permanent Operating current Current consumption at U _{cpv}	I _{cpv}	None	Follow current	I _f	None	Nominal discharge current 15 x 8/20 μs impulses	I _n	20 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	40 kA	Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max} Total	60 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U _{oc}	6 kV	Current withstand short circuit PV	I _{scpv}	15 000 A	Connection mode(s)		+/-/PE	Protection mode(s)		Common/Differential mode	Protection level +/- @ I _n (8/20μs)	U _p	4.3 kV	Protection level +/-PE (-/PE) @ I _n (8/20μs)	U _p	4.3 kV	Protection level at 5 kA @ 5 kA (8/20μs)	U _p	3,5 kV	Protection level at U _{oc} @ U _{oc} (1.2/50 μs)	U _p	3,1 kV
SPD type		2+3																																																						
Network		PV 1200 Vdc																																																						
Nominal PV voltage	U _{ocstc}	1000 Vdc																																																						
Max. PV operating voltage	U _{cpv}	1200 Vdc																																																						
Residual Current Leakage current to Ground	I _{pe}	None																																																						
PV Permanent Operating current Current consumption at U _{cpv}	I _{cpv}	None																																																						
Follow current	I _f	None																																																						
Nominal discharge current 15 x 8/20 μs impulses	I _n	20 kA																																																						
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	40 kA																																																						
Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max} Total	60 kA																																																						
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U _{oc}	6 kV																																																						
Current withstand short circuit PV	I _{scpv}	15 000 A																																																						
Connection mode(s)		+/-/PE																																																						
Protection mode(s)		Common/Differential mode																																																						
Protection level +/- @ I _n (8/20μs)	U _p	4.3 kV																																																						
Protection level +/-PE (-/PE) @ I _n (8/20μs)	U _p	4.3 kV																																																						
Protection level at 5 kA @ 5 kA (8/20μs)	U _p	3,5 kV																																																						
Protection level at U _{oc} @ U _{oc} (1.2/50 μs)	U _p	3,1 kV																																																						
	Mechanical Characteristics																																																							
	<table border="1"> <tr><td>Technology</td><td></td><td>VG Technology (MOV+GSG)</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 2.5-25mm² (35mm²) / by bus</td></tr> <tr><td>Format</td><td></td><td>Compact monobloc box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>T_u</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>All pole disconnection from PV network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator - Red/Green</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr><td>Max. Voltage/Current for remote signaling</td><td></td><td>250 V / 0.5 A (AC) / 30 V / 3 A (DC)</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram - 2.5TE (EN43880)</td></tr> <tr><td>Weight</td><td></td><td>0.285 kg</td></tr> </table>		Technology		VG Technology (MOV+GSG)	Connection to Network		By screw terminals: 2.5-25mm ² (35mm ²) / by bus	Format		Compact monobloc box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	T _u	-40/+85°C	Protection rating		IP20	Failsafe mode		All pole disconnection from PV network	Disconnection indicator		1 mechanical indicator - Red/Green	Remote signaling of disconnection		Output on changeover contact	Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	Dimensions		See diagram - 2.5TE (EN43880)	Weight		0.285 kg															
Technology		VG Technology (MOV+GSG)																																																						
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ²) / by bus																																																						
Format		Compact monobloc box																																																						
Mounting		Symmetrical rail 35 mm (EN 60715)																																																						
Housing material		Thermoplastic UL94 V-0																																																						
Operating temperature	T _u	-40/+85°C																																																						
Protection rating		IP20																																																						
Failsafe mode		All pole disconnection from PV network																																																						
Disconnection indicator		1 mechanical indicator - Red/Green																																																						
Remote signaling of disconnection		Output on changeover contact																																																						
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																																						
Dimensions		See diagram - 2.5TE (EN43880)																																																						
Weight		0.285 kg																																																						
	Disconnectors																																																							
	<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>CTC Technology integrated</td></tr> <tr><td>Back-up protection device</td><td></td><td>Without</td></tr> </table>		Thermal disconnector		CTC Technology integrated	Back-up protection device		Without																																																
Thermal disconnector		CTC Technology integrated																																																						
Back-up protection device		Without																																																						
	Standards																																																							
	<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5</td></tr> <tr><td>Certification</td><td></td><td>KEMA</td></tr> </table>		Standards compliance		IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5	Certification		KEMA																																																
Standards compliance		IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5																																																						
Certification		KEMA																																																						
	Part number																																																							
	65122102																																																							

