



## 2-pair Data surge protector unit

# CITEL

## B280-48DBC



- 2-pair surge protection unit
- 48 V
- Removable protection circuit
- Wall mounting and screw connection
- UL497 A&B



	<b>Electrical Characteristics</b>																																					
<p>Gb: 3-electrode gas tube R: Resistor DBC: 3-pole low capacitance diode</p>	<b>Mechanical Characteristics</b>																																					
	<table border="1"> <tbody> <tr><td>Network</td><td></td><td>RNIS-T0, 48 V line</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>48 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>53 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>&gt; 20 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>&lt; 1 dB</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/L</td><td>75 V</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/PE</td><td>20 V</td></tr> <tr><td>Line resistance</td><td></td><td>&lt; 4.7 Ohm</td></tr> </tbody> </table>	Network		RNIS-T0, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss		< 1 dB	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Protection mode(s)		Common/Differential mode	Protection level @ In (8/20 μs)	Up L/L	75 V	Protection level @ In (8/20 μs)	Up L/PE	20 V	Line resistance		< 4.7 Ohm							
Network		RNIS-T0, 48 V line																																				
Nominal line voltage	Un	48 V																																				
Max. DC operating voltage	Uc	53 Vdc																																				
Max. frequency	f max.	> 20 MHz																																				
Insertion loss		< 1 dB																																				
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																				
Protection mode(s)		Common/Differential mode																																				
Protection level @ In (8/20 μs)	Up L/L	75 V																																				
Protection level @ In (8/20 μs)	Up L/PE	20 V																																				
Line resistance		< 4.7 Ohm																																				
	<table border="1"> <tbody> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>2 pairs</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.4-1.5mm<sup>2</sup></td></tr> <tr><td>Format</td><td></td><td>Wall mounting box</td></tr> <tr><td>Mounting</td><td></td><td>Wall mounting by screws (not supplied)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit - transmission cut-off - fault mode 2</td></tr> <tr><td>Spare module(s)</td><td></td><td>S280-48DBC</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.043 kg</td></tr> </tbody> </table>		Technology		GDT+Clamping diode	SPD configuration		2 pairs	Connection to Network		By screw terminal: cross section 0.4-1.5mm <sup>2</sup>	Format		Wall mounting box	Mounting		Wall mounting by screws (not supplied)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit - transmission cut-off - fault mode 2	Spare module(s)		S280-48DBC	Dimensions		See diagram	Weight		0.043 kg
Technology		GDT+Clamping diode																																				
SPD configuration		2 pairs																																				
Connection to Network		By screw terminal: cross section 0.4-1.5mm <sup>2</sup>																																				
Format		Wall mounting box																																				
Mounting		Wall mounting by screws (not supplied)																																				
Housing material		Thermoplastic UL94 V-0																																				
Operating temperature	Tu	-40/+85°C																																				
Protection rating		IP20																																				
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2																																				
Spare module(s)		S280-48DBC																																				
Dimensions		See diagram																																				
Weight		0.043 kg																																				
	<table border="1"> <tbody> <tr><td colspan="3"><b>Standards</b></td></tr> <tr><td>Standards compliance</td><td></td><td>IEC 61643-21 / EN 61643-21 / UL497A</td></tr> <tr><td>Certification</td><td></td><td>UL 497B</td></tr> <tr><td colspan="3"><b>Part number</b></td></tr> <tr><td colspan="3">72754</td></tr> </tbody> </table>		<b>Standards</b>			Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A	Certification		UL 497B	<b>Part number</b>			72754																							
<b>Standards</b>																																						
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A																																				
Certification		UL 497B																																				
<b>Part number</b>																																						
72754																																						

