



- High speed data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																								
<p>P : 3-poliger Gasableiter Pb : 2-poliger Gasableiter R : Widerstand oder Spule D : Diode</p> <p>G : 3-electrode gas tube Gb : 2-electrode gas tube R : Resistor D : Clamping diode</p>	<table border="1"> <tr><td>Network</td><td></td><td>RS232, RS485</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>12 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>15 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>10 kA</td></tr> <tr><td>Line inductance</td><td></td><td>No</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/L</td><td>30 V</td></tr> <tr><td>Impulse current 2 x 10/350 μs Test - D1 Category</td><td>limp</td><td>2.5 kA</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>In L/L</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category</td><td>In L/PE</td><td>5 kA</td></tr> <tr><td>Line resistance</td><td></td><td>< 4.7 Ohm</td></tr> </table>		Network		RS232, RS485	Nominal line voltage	Un	12 V	Max. DC operating voltage	Uc	15 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA	Line inductance		No	Protection level @ In (8/20 μs)	Up L/L	30 V	Impulse current 2 x 10/350 μs Test - D1 Category	limp	2.5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		< 4.7 Ohm
Network		RS232, RS485																																							
Nominal line voltage	Un	12 V																																							
Max. DC operating voltage	Uc	15 Vdc																																							
Max. frequency	f max.	> 3 MHz																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	300 mA																																							
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA																																							
Line inductance		No																																							
Protection level @ In (8/20 μs)	Up L/L	30 V																																							
Impulse current 2 x 10/350 μs Test - D1 Category	limp	2.5 kA																																							
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																							
Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	In L/PE	5 kA																																							
Line resistance		< 4.7 Ohm																																							
	Mechanical Characteristics																																								
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>1-pair+shielded</td></tr> <tr><td>Connection to Network</td><td></td><td>By spring terminal - max. cross section 2.5mm² / AWG 13 (solid or stranded)</td></tr> <tr><td>Format</td><td></td><td>DIN box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Ingress Protection rating</td><td></td><td>IP20 (NEMA 2)</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>Disconnection indicator</td><td></td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Spare module(s)</td><td></td><td>DLAM-06D3</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.029 kg</td></tr> </table>		Technology		GDT+Clamping diode	SPD configuration		1-pair+shielded	Connection to Network		By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)	Format		DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Ingress Protection rating		IP20 (NEMA 2)	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLAM-06D3	Dimensions		See diagram	Weight		0.029 kg
Technology		GDT+Clamping diode																																							
SPD configuration		1-pair+shielded																																							
Connection to Network		By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)																																							
Format		DIN box																																							
Mounting		Symmetrical rail 35 mm (EN 60715)																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating temperature	Tu	-40/+85°C																																							
Ingress Protection rating		IP20 (NEMA 2)																																							
Failsafe mode		Short-circuit																																							
Disconnection indicator		Transmission interrupt - default mode 2																																							
Spare module(s)		DLAM-06D3																																							
Dimensions		See diagram																																							
Weight		0.029 kg																																							
	Standards																																								
	<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-21 / EN 61643-21 / UL497B</td></tr> <tr><td>Certification</td><td></td><td>UL 497B</td></tr> </table>		Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B	Certification		UL 497B																																	
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B																																							
Certification		UL 497B																																							
	Part number																																								
	641102																																								

