


MSP-VM24/R



- Security camera surge protector
- AC + Cat.5 (connector RJ45)
- Compact aluminium housing
- Rail DIN mounting or plate



Electrical Characteristics

SPD type		2+3
Network		24 Vac/Vdc
Nominal line voltage	Un	24 Vac/Vdc
Max. DC operating voltage	Uc	30 Vac/Vdc
Insertion loss		< 1 dB
Max. load current	IL	5 A
Nominal discharge current 15 x 8/20 μ s impulses	In	5 kA
Max. discharge current max. withstand @ 8/20 μ s by pole	Imax	10 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50 μ s - 8/20 μ s	Uoc	10 kV / 5 kA
Protection mode(s)		Common/Differential mode
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	220 V
Protection level L/N @ In (8/20 μ s)	Up L/N	20 V
Protection level L/PE @ In (8/20 μ s)	Up L/PE	20 V
Nominal discharge current C2 Category	In	2.5 kA

ELEC

Protection level @ In (8/20 μ s)	Up	20 V
--------------------------------------	----	------

ELEC

Network		4 pairs Ethernet 100 Base-TX
---------	--	------------------------------

ELEC

Max. DC operating voltage	Uc	8 Vdc
---------------------------	----	-------

ELEC

Max. frequency	f max.	125 MHz
----------------	--------	---------

ELEC

Insertion loss		< 1dB
----------------	--	-------

ELEC

Max. load current	IL	300 mA
-------------------	----	--------

ELEC

Max. discharge current max. withstand @ 8/20 μ s by pole	Imax	5 kA
--	------	------

ELEC

Protection level @ In (8/20 μ s)	Up	20 V
--------------------------------------	----	------

ELEC

Protection level L/N @ In (8/20 μ s)	Up L/N	20 V
--	--------	------

ELEC

Protection level L/PE @ In (8/20 μ s)	Up L/PE	20 V
---	---------	------

ELEC

Nominal discharge current C2 Category	In	2.5 kA
---------------------------------------	----	--------

Mechanical Characteristics

Technology		MOV+GDT
Connection to Network		By screw terminals: 2.5mm ² max.
Format		DIN rail or flange
Mounting		DIN rail or plate (flange)
Housing material		Anodized aluminum
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection and Power cut off
Disconnection indicator		Green LED OFF and line cut off
Voltage/operating indicator		Green Led ON
Dimensions		See diagram

Disconnectors

Thermal disconnector		Internal
----------------------	--	----------

Standards

MSP-VM24/R

Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Part number	
420412	

