



CITEL

1-pair monobloc Data surge protector

DLU-24D3



- For DIN rail mounting
- Monobloc housing
- 1-pair
- Un: 24 V
- Transmission an protection of shield wire
- IEC 61643-21 compliance
- UL497A



	Electrical Characteristics	
	Network	4-20mA, Liaison 24V
Nominal line voltage	Un	24 V
Max. DC operating voltage	Uc	28 Vdc
Max. frequency	f max.	> 3 MHz
Insertion loss		< 1 dB
Max. load current @25°C	IL	300 mA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA
Line inductance		No
Protection mode(s)		Common/Differential mode
Protection level @ In (8/20 μs)	Up L/L	40 V
Max. capacitance	C	< 50 pF
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA
Nominal discharge current C2 Category	In	5 kA
Line resistance		< 4.7 Ohm
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	Mechanical Characteristics	
	Technology	
SPD configuration		1-pair+shielded
Connection to Network		By screw terminal - cross section 1.5-2.5mm ²
Format		DIN box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit
Disconnection indicator		Transmission interrupt - default mode 2
Dimensions		See diagram
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497 A
Certification		UL 497B
Part number		
640503		

